

PRODUCT NO. 4970-030040

DOTLUX LED downlight CIRCLEmini-AC 5W 3000K UGR<19



to the product page

- Glare-free luminaire design (UGR>19).
- Perfectly suitable for refurbishments due to the low mounting depth and relatively large aperture
- Easy installation due to the integrated power supply unit and the 15 cm connection cable
- Flexible illumination due to swiveling LED unit

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.065
POWER CONSUMPTION IN WATTS	5
NET LUMINOUS FLUX IN LUMENS	400
LUMEN PER WATT	80

Dimensions

height: 44mm
diameter: 85mm

BEAM ANGLE	40°
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 20.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,5
INRUSH CURRENT IN A	0
IK protection	
LUMEN PER WATT	80
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
GLARE-FREE	UGR < 19
INSTALLATION OPENING DIAMETER IN MM	68-75
WARRANTY IN YEARS	2
L80/B10	30000
RATED CURRENT	0.07
SUITABLE FOR SURFACE MOUNTING	No
SUITABLE FOR MOUNTING	Yes
ASSORTMENT	Ecoline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	30000

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	15000
ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
LAMP HOLDER	without
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Reflector
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK02
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Through wiring included
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	No
SUITABLE FOR LIGHT-TRACK MOUNTING	No
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	No

EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	15000
LIFETIME L90/B10 AT 25°C	60000
PULSE DURATION IN µs	0
LIFETIME L90/B50 AT 25°C	50000
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
ADJUSTABILITY	Swivelling
SURFACE PROTECTION	Plastic-coated
REFLECTOR	High-gloss
BEAM ANGLE	Medium beam 21-40°
MATERIAL COVER	Without cover
CONNECTION TYPE	Other