

PRODUCT NO. 1665-230360

DOTLUX LED street lamp RETROFITprotect E27 18W 3000K













- Overvoltage protection up to 4,000 V
- No early failures: SecureSolderConnect technology prevents hairline cracks and cold solder
- Unique: Integrated, temperature-dependent power regulation to 50% to protect against overheating
- AirFin-Cooling: 2.5 times larger cooling surface than comparable products and up to 20% reduced weight at lamp base
- Easy replacement with Retro-Fit E27 base for common HQL/NAV lamps
- Lamp can be operated without conversion on HQL Voschlat devices and also directly on 230V. NAV ballasts must be disconnected
- Optimally arranged LEDs enable uniform light distribution
- Lamp efficiency of up to 130 lm / W due to the use of high quality Lm80 certified LEDs

() EN	ERG*
DOTLUX 1665-230360)
A	
В	
С	
D E	D
F	
G	
18 kWh/1000h	2019/2015 1 2 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4

SUCCESSION ARTICLE	-	BEAM ANGLE	360°
PREDECESSOR ARTICLE	1665-130360	PROTECTION CLASS (IP)	IP40
		INPUT VOLTAGE	100 -
WEIGHT IN KG	0.212	SERVICE LIFE	appr

POWER CONSUMPTION IN WATTS 18 **NET LUMINOUS FLUX IN LUMENS** חחלכ **LUMEN PER WATT** 150

Dimensions

height: 166mm diameter: 73mm

- 240 V AC orox. 35.000 h at 25°C BASE E27 **COLOR TEMPERATURE IN KELVIN** 2000 **COLOR-RENDERING-INDEX** CRI > 80 **POWER FACTOR** 0,9 **INRUSH CURRENT IN A** 45 **LUMEN PER WATT** 150 **HOUSING COLOUR** white **SWITCH CYCLES** > 70.000 WARRANTY IN YEARS ENEC-CERTIFIED ENEC 25 **ENERGY EFFICIENCY CLASS**

ACCORDING TO EU REGULATION 2019/2015

ETIM GRUPPEN-ID EC001959 **COLOUR CONSISTENCY (MCADAM** SDCM6 LIFETIME L90/B10 AT 25°C 12500

PULSE DURATION IN μS LIGHT COLOUR ACCORDING TO EN

12464-1

LIFETIME L90/B50 AT 25°C

BEG FUNDING Only relevant in Germany

50

16667

COLOUR White

warm white <3300 K