

PRODUCT NO. 1665-230360NANO

DOTLUX LED street lamp RETROFITnano E27 18W 3000K















to the product page

- Waterproof nano-coating IP65 with fully potted driver module.
- Overvoltage protection up to 4,000 V
- No early failures: SecureSolderConnect technology prevents hairline cracks and cold solder joints
- Unique: Integrated, temperature-dependent power regulation to 50% to protect against overheating
- AirFin-Cooling: 2.5 times larger cooling surface than comparable products and up to 20% reduced weight at lamp base
- Easy replacement with Retro-Fit E27 base for common HQL/NAV lamps
- Lamp can be operated without conversion on HQL Voschlat devices and also directly on 230V.
 NAV ballasts must be disconnected
- Optimally arranged LEDs enable uniform light distribution
- Lamp efficiency of up to 130 lm / W due to the use of high quality Lm80 certified LEDs

O EN	ERG*
DOTLUX 1665-230360NANO	
A	
В	
С	
D	D
E	
F	
G	
18 kWh/1000h	2019/2015

SUCCESSION ARTICLE	-	BEAM ANGLE	360°
PREDECESSOR ARTICLE	1665-130360NANO	PROTECTION CLASS (IP)	IP65
		INPUT VOLTAGE	100 - 240 V AC
WEIGHT IN KG	0.35	SERVICE LIFE	approx. 50.000 h at 25°C
POWER CONSUMPTION IN WATTS	18	BASE	E27
NET LUMINOUS FLUX IN LUMENS	2700	COLOR TEMPERATURE IN KELVIN	3000
LUMEN PER WATT	150	COLOR-RENDERING-INDEX	CRI > 80
		POWER FACTOR	0,9
		INRUSH CURRENT IN A	45

Dimensions

height: 166mm diameter: 73mm LUMEN PER WATT 150
HOUSING COLOUR white
SUITED FOR EMERGENCY LIGHTING yes
SWITCH CYCLES > 100.000
WARRANTY IN YEARS 5

ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATIOND

ENEC-CERTIFIED

ACCORDING TO EU REGULATION D

ETIM GRUPPEN-ID EC001959

COLOUR CONSISTENCY (MCADAM ELLIPSE)

SULTABLE FOR EMERGENCY LIGHTING YOU

SUITABLE FOR EMERGENCY LIGHTINGYesLIFETIME L90/B10 AT 25°C17000PULSE DURATION IN µS50

LIGHT COLOUR ACCORDING TO EN 12464-1

LIFETIME L90/B50 AT 25°C

BEG FUNDING Only relevant in Germany

19.04.2024 Page 1/2 Product no.: 1665-230360NANO

warm white <3300 K

22667

ENEC 05



COLOUR White