

PRODUCT NO. 3487-040170

DOTLUX QUICK-FIXplus 16 4 W neutral white 4000K LED interchangeable module (with 4 W emergency lighting module with separate connection)













- Universal MAGNET LED module with integrated driver for quick and easy replacement of light sources in existing ceiling and wall luminaires
- Extra high magnetic feet enable installation above the existing cabling
- Very high efficiency of up to 120lm/W thanks to low-current LEDs and therefore long service life
- Our QUICK-FIXplus luminaires comply with DIN EN60598-2-22:2014, a standard that confirms approval in the field of emergency lighting.
- Special lenses with 170° beam angle ensure absolutely shadow-free light distribution even in larger luminaires up to 400mm
- Integrated 4W emergency lighting module with separate power supply unit suitable for central battery

to the product page	
○ ENERG*	
DOTLUX	
3487-040170	
A	
В	
C	
D	
E	Œ
F	
G	
16 kWh/1000h	2019/2015 10 44 44 44 44 44 44 44 44 44 44 44 44 44

WEIGHT IN KG
POWER CONSUMPTION IN WATTS
NET LUMINOUS FLUX IN LUMENS
LUMEN PER WATT

0.2 16 + 4

1900lm (+4W 450lm)

119

 BEAM ANGLE
 170°

 PROTECTION CLASS (IP)
 IP20

 TEMPERATURE RANGE
 -40°C to +50°C

SERVICE LIFE approx. 40.000 h at 25°C

 COLOR TEMPERATURE IN KELVIN
 4000

 COLOR-RENDERING-INDEX
 CRI > 82

 LUMEN PER WATT
 119

 VOLTAGE TYPE
 AC/DC

 SWITCH CYCLES
 > 80.000

 INPUT VOLTAGE SPAN
 176-240 V AC/DC

WARRANTY IN YEARS 3

WARRANTT IN TEARS

INPUT VOLTAGE RANGE LUMINAIRE 176-240 V AC/DC

Cable

ENERGY EFFICIENCY CLASS
ACCORDING TO EU REGULATION E
2019/2015

ETIM GRUPPEN-ID EC000996

COLOUR CONSISTENCY (MCADAM SDCM4

CONNECTION TYPE

PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471 RG1
COMPATIBLE WITH APPLE HOMEKIT No

COMPATIBLE WITH GOOGLE
ASSISTANT

COMPATIBLE WITH AMAZON ALEXA No
IFTTT SUPPORT AVAILABLE No
FLEXIBLE Nein

Dimensions

height: 68mm diameter: 180mm



SUITABLE FOR TRAFFIC LIGHTS NO
EXTERNAL DRIVER REQUIRED NO
SUITABLE FOR CONSTANT VOLTAGE Yes
SUITABLE FOR GENERAL LIGHTING Yes
SUITABLE FOR RAIL TRAFFIC NO
SUITABLE FOR MATRIX INFORMATION NO
BOARDS

SUITABLE FOR VARIABLE ROAD SIGNS No

LIGHT COLOUR ACCORDING TO EN 12464-1

neutral white 3300 to 5300 K

BEG FUNDING Only relevant in Germany

LED-BETRIEBSSTROM IN MA90SHAPERoundCOLOURWhite