

PRODUCT NO. 5043

**LED power supply CC for QUICK-FIXdc 15-50W 350-1400mA 25-54V non-dimmable NFC linear pre-programmed outputs 350/700/1050/1400mA**



to the product page

- SELV output protection for safety and flexibility in luminaires
- Very low current ripple, in accordance with the IEEE 1789 recommendation
- NFC technology for wireless programming
- Wide selection range for the fixed current output
- Suitable for use in emergency lighting applications
- Active open-circuit protection
- Long service life of up to 100,000 hours
- Ideal solution for class I and class II luminaires
- Adjustable operating current: 350/700/1050/1400mA

**PRODUCT GROUP** EC002710\_LED-Betriebsgerät

**SUCCESSION ARTICLE** -  
**PREDECESSOR ARTICLE** 4226

**WEIGHT IN KG** 0.198  
**POWER CONSUMPTION IN WATTS** 15-50

<b>PROTECTION CLASS (IP)</b>	IP20
<b>INPUT VOLTAGE</b>	186 - 240 AC/DC
<b>INRUSH CURRENT IN A</b>	0
<b>TC TEMPERATURE IN °C</b>	80
<b>PROTECTION CLASS</b>	II
<b>OVERVOLTAGE PROTECTION</b>	1000 V
<b>OUTPUT VOLTAGE</b>	25-54
<b>INPUT VOLTAGE SPAN</b>	198-264 AC / 186-280 DC
<b>WARRANTY IN YEARS</b>	5
<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	198-264 AC / 186-280 DC
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No

**Dimensions**

**length:** 280mm  
**width:** 30mm  
**height:** 21mm

<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>ELDAS-NR.</b>	941007729
<b>DIAMETER IN MM</b>	0
<b>ABMESSUNGEN BREITE MM</b>	30
<b>ABMESSUNGEN HÖHE MM</b>	21
Ausgangsstrom in A	
<b>MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16</b>	28
<b>MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16</b>	46