

PRODUCT NO. 3679-1

DOTLUX LED safety light EXITtop with self-test incl. 2 interchangeable lenses white 3h



to the product page

- Universally mountable safety light for recessed and surface mounting
- Replaceable rechargeable battery with a light duration of 3 hours
- Integrated push-button and control LED for operating status display
- Only suitable for standby mode. If the light is supplied with mains power, the integrated rechargeable battery charges and the light is in standby mode.
- Incl. two easy-to-change lenses
- Corridor lighting (asymmetrical)
- Wide beam
- Automatic self-test function

PRODUCT GROUP EC001957_Sicherheitsleuchte

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 3679 3679-1

WEIGHT IN KG 0.433
POWER CONSUMPTION IN WATTS 0,5
NET LUMINOUS FLUX IN LUMENS 240

Dimensions

length: 140mm
width: 140mm
height: 62mm
diameter: 140mm

BEAM ANGLE 180
PROTECTION CLASS (IP) IP20
INPUT VOLTAGE 220 - 240 AC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 5000
POWER FACTOR 0,25
BATTERY RUNTIME 3h
PROTECTION CLASS II
VOLTAGE TYPE AC
HOUSING COLOUR white
SUITED FOR EMERGENCY LIGHTING yes
PICTOGRAM INCLUDED No
INSTALLATION OPENING WIDTH IN MM 0
INSTALLATION OPENING LENGTH IN MM 0
INPUT VOLTAGE SPAN 220-240 AC
WARRANTY IN YEARS 3
L80/B10 50000
DIMMING WITHOUT DIMMER No
INPUT VOLTAGE RANGE LUMINAIRE 220-240 AC
SELF-TEST Automatic self-test
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 not required
LIFETIME L80/B10 AT 25°C 50000

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
WITH ILLUMINANT	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	-
TYPE OF CONTROL GEAR	LED operating device voltage-controlled
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	Yes
CONSTANT LIGHT OUTPUT (CLO)	No
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED not exchangeable
MOUNTING METHOD	Built-in
WITH REMOTE CONTROL	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	G
ELDAS-NR.	941009679
Dimension Length in mm	
DIAMETER IN MM	140
MAX. SYSTEM POWER IN W	0,5
ABMESSUNGEN BREITE MM	140
ABMESSUNGEN HÖHE MM	62
NOMINAL VOLTAGE IN V	230
TYPE OF WIRING	Suitable for through wiring
MATERIAL COVER	Other