

CASAMBI DALI interface/gateway passive

Order number: 5116

CASAMBI to DALI gateway

Ideal for DALI group control (max. 64DALI devices with DALI power supply Art.5119)

- Up to 250 DALI devices per interface depending on the DALI power supply (max. 250mA=249 devices)
- Through-wirable DALI interface for convenient control of DALI light sources via Casambi app
- Suitable for integrating a conventional DALI sensor into the CASAMBI world
- passive device, external power supply via DALI cable required! Compatible with DALI power supply (item no. 5119)
- compatible with sensor (art. no. 5117), radio remote control (art. no. 5120) and wall switch (art. no. 5121)
- Various pre-installed profiles can be selected in the CASAMBI app
- Control of DALI components via CASAMBI
- Control of CASAMBI components via DALI
- DALI individual addressing or DALI group control/broadcast
- Complete control via CASAMBI app:
- Control of brightness and light color
- Configuration of luminaires and luminaire networks
- Creating scenes and animations (color gradients)
- Intelligent timer and gallery functions

protection class (IP): IP20; Input voltage span: 9,5-22,5 V DC; Input voltage range luminaire: 9.5-22.5 V DC; ETIM Gruppen-ID: EC002924;
BEG funding: Only relevant in Germany
width: 36mm