


PRODUCT NO. 3140-1

LED power supply CC 9-15W 200-350mA 16W 26-42V dimmable Phase cut-off



to the product page

- The power supply unit is dimmable via trailing edge phase dimmers
- With constant current technology (CC), it is suitable for luminaires with constant current
- The connected constant current luminaires can be dimmed between 10%-100%
- Suitable dimmers: JUNG 1224 LED UDE, Eltako EUD61NPL-230V, GIRA Mini2440 00 and many more.
- The output current is adjustable: 200/250/300/350mA
- The power supply unit is set to 200mA as standard

PRODUCT GROUP	EC002710_LED-Betriebsgerät	PROTECTION CLASS (IP)	IP20
SUCCESSION ARTICLE	-	INPUT VOLTAGE	220 - 240 AC
PREDECESSOR ARTICLE	3140	POWER FACTOR	0,98
WEIGHT IN KG	0.079	INRUSH CURRENT IN A	0
POWER CONSUMPTION IN WATTS	9-15	TC TEMPERATURE IN °C	85
Dimensions		PROTECTION CLASS	II
length: 122mm		OVERVOLTAGE PROTECTION	1000 V
width: 41mm		OUTPUT VOLTAGE	26 - 42 DC
height: 23mm		INPUT VOLTAGE SPAN	180-264 AC
		WARRANTY IN YEARS	5
		INPUT VOLTAGE RANGE LUMINAIRE	180-264 AC
		DIMMING MAINS VOLTAGE MODULATION	Yes
		DIMMING PHASE CUT-OFF	Yes
		NO DIM FUNCTION	No
		COMPATIBLE WITH CASAMBI	No
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No
		DIMMING PHASE CUT-ON	Yes
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany
		ELDAS-NR.	941934299
		DIAMETER IN MM	0

ABMESSUNGEN BREITE MM

41

ABMESSUNGEN HÖHE MM

23

Ausgangsstrom in A