

PRODUCT NO. 5158-040155

DOTLUX LED street light DOLPHINmini 150W 4000K 1-10V dimmable without pole adapter



to the product page

- Technical light with feel-good guarantee thanks to higher color rendering and two light colors
- Protection class I with integrated overvoltage protection (10,000 V)
- Universal mounting, pole attachment/attachment on all pole diameters 42-76 mm, pivotable +/-15°
- Multilayer lens optics with Lumileds® LEDs enable uniform light distribution
- Solid cast aluminum housing similar to RAL 9006 with pressure equalization valve
- Reliable and highly efficient LED driver with a service life of > 50,000 h ensures low maintenance costs
- Easy installation and tool-free maintenance thanks to disconnect plug
- Power reduction via separately available module (80%, 60%, 40%, 20%)

PRODUCT GROUP	EC000062_Straßen- und Platzleuchte		
WEIGHT IN KG	7.15	BEAM ANGLE	155x45
POWER CONSUMPTION IN WATTS	150	PROTECTION CLASS (IP)	IP66
NET LUMINOUS FLUX IN LUMENS	19750	LIGHT COLOR	white
LUMEN PER WATT	132	INPUT VOLTAGE	220 - 240 AC
		SERVICE LIFE	approx. 80.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 82
Dimensions		MAST SUPPORT	depending on adapter
length: 630mm		POWER FACTOR	0,95
width: 336mm		INRUSH CURRENT IN A	0
height: 132mm		IK PROTECTION	IK08
		LUMEN PER WATT	132
		VOLTAGE TYPE	AC
		HOUSING COLOUR	gray
		SUITED FOR EMERGENCY LIGHTING	No
		OVERVOLTAGE PROTECTION	up to 10000 V
		WARRANTY IN YEARS	5
		L80/B10	50000
		DIMMING WITHOUT DIMMER	No
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	50000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
		WITH ILLUMINANT	Yes

LAMP HOLDER	-
MATERIAL COVER	Glass transparent
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	Yes
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH LIGHT SENSOR	No
TYPE OF WIRING	Ending
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
EXCHANGEABLE CONTROL GEAR	No
Suitable for lamp power in w	
LAMP TYPE	LED exchangeable
MOUNTING METHOD	essay
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	E
ELDAS-NR.	941742499
Dimension Length in mm	
DIAMETER IN MM	0
MAX. SYSTEM POWER IN W	150
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-30-50
ABMESSUNGEN BREITE MM	336
ABMESSUNGEN HÖHE MM	132

NOMINAL VOLTAGE IN V	230
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	6
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	10
SURFACE PROTECTION	Powder coating
LIGHT DISTRIBUTOR	None
CONNECTION TYPE	Other