

PRODUCT NO. 5180

DOTLUX LED rotary dimmer 5-100W dimmable trailing edge phase control



to the product page



- The LED rotary dimmer is compatible with trailing edge phase dimmable LED luminaires
- With constant current technology (CC), it is suitable for luminaires with constant current
- The connected constant current luminaires can be dimmed between 1%-100
- Suitable for the following systems:
 - Berker by Hager
 - Busch-Jaeger
 - GIRA
 - JUNG
 - Merten by Schneider
 - NIKO
 - PEHA
 - Exxact
 - ELKO RS

PRODUCT GROUP	EC002924_Steuergerät für Leuchten	PROTECTION CLASS (IP)	IP20
SUCCESSION ARTICLE	-	INPUT VOLTAGE	220 - 240 AC
PREDECESSOR ARTICLE	3587	PROTECTION CLASS	none
WEIGHT IN KG	0.064	OUTPUT VOLTAGE	200
POWER CONSUMPTION IN WATTS	5 - 100	WARRANTY IN YEARS	3
Dimensions		CONTROL METHOD	Sine Wave Reduction
height: 25mm		SUITABLE FOR MOUNTING	No
length: 71mm		DIMMING WITHOUT DIMMER	No
width: 71mm		COMPATIBLE WITH CASAMBI	No
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No
		SURFACE-MOUNTED	No
		MODEL	Dynamic
		DIN-RAIL MOUNTING	No
		BUILT-IN	Yes
		SUITABLE FOR OUTDOOR USE	No
		HOUSING	Plastic housing
		PROGRAMMABLE	No
		SUITABLE FOR CASAMBI	No
		SUITABLE FOR DOTLUX FUSION	No
		SUITABLE FOR KEY OPERATION	No
		SUITABLE FOR TUYA	No
		BEG FUNDING	Only relevant in Germany

ELDAS-NR.	941999949
DIAMETER IN MM	0
ABMESSUNGEN BREITE MM	71
ABMESSUNGEN HÖHE MM	25