

PRODUCT NO. 5188

**LED power supply unit CV 24V DC 0-100W 0-4.2A non-dimmable IP20 linear**



to the product page

- The power supply unit is not dimmable
- With constant voltage technology (CV), it is suitable for luminaires with constant voltage

**PRODUCT GROUP** EC002710\_LED-Betriebsgerät

**SUCCESSION ARTICLE** -

**WEIGHT IN KG** 0.304

**POWER CONSUMPTION IN WATTS** 0-100

**Dimensions**

**length:** 360mm

**width:** 30mm

**height:** 21mm

|  |              |
|--|--------------|
| <b>PROTECTION CLASS (IP)</b>                     | IP20         |
| <b>INPUT VOLTAGE</b>                             | 220 - 240 AC |
| <b>POWER FACTOR</b>                              | 0,98         |
| <b>INRUSH CURRENT IN A</b>                       | 0            |
| <b>TC TEMPERATURE IN °C</b>                      | 85           |
| <b>PROTECTION CLASS</b>                          | I            |
| <b>OVERVOLTAGE PROTECTION</b>                    | 2000 V       |
| <b>OUTPUT VOLTAGE</b>                            | 24 DC        |
| <b>WARRANTY IN YEARS</b>                         | 3            |
| <b>DIMMING WITHOUT DIMMER</b>                    | No           |
| <b>DIMMING 0-10 V</b>                            | No           |
| <b>DIMMING 1-10 V</b>                            | No           |
| <b>DIMMING DALI</b>                              | No           |
| <b>DIMMING DMX</b>                               | No           |
| <b>DIMMING DSI</b>                               | No           |
| <b>DIMMING POTENTIOMETER (INTEGRATED)</b>        | No           |
| <b>DIMMING LINESWITCH</b>                        | No           |
| <b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b> | No           |
| <b>DIMMING MAINS VOLTAGE MODULATION</b>          | No           |
| <b>DIMMING PHASE CUT-OFF</b>                     | No           |
| <b>DIMMING PROGRAMMABLE</b>                      | No           |
| <b>DIMMING RF</b>                                | No           |
| <b>DIMMING SINE WAVE REDUCTION</b>               | No           |

|  |                          |
|--|--------------------------|
| <b>DIMMING TOUCH AND DIM</b>                                     | No                       |
| <b>DIMMING ZIGBEE</b>  | No                       |
| <b>DIMMING WITH PUSH-BUTTON</b>                                  | No                       |
| <b>NO DIM FUNCTION</b>   | Yes                      |
| <b>CONSTANT LIGHT OUTPUT (CLO)</b>                               | No                       |
| <b>COMPATIBLE WITH CASAMBI</b>                                   | No                       |
| <b>COMPATIBLE WITH APPLE HOMEKIT</b>                             | No                       |
| <b>COMPATIBLE WITH GOOGLE ASSISTANT</b>                          | No                       |
| <b>COMPATIBLE WITH AMAZON ALEXA</b>                              | No                       |
| <b>IFTTT SUPPORT AVAILABLE</b>                                   | No                       |
| <b>SUITABLE FOR CONSTANT VOLTAGE</b>                             | Yes                      |
| <b>SUITABLE FOR CONSTANT CURRENT</b>                             | No                       |
| <b>DIMMING PHASE CUT-ON</b>                                      | No                       |
| <b>DIMMING GPRS</b>  | No                       |
| <b>PULSE DURATION IN <math>\mu</math>S</b>                       | 0                        |
| <b>BEG FUNDING</b>   | Only relevant in Germany |
| <b>ELDAS-NR.</b>   | 941934329                |
| <b>DIAMETER IN MM</b>  | 0                        |
| <b>RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C</b> | -25-50                   |
| <b>ABMESSUNGEN BREITE MM</b>                                     | 30                       |
| <b>ABMESSUNGEN HÖHE MM</b>                                       | 21                       |
| <b>AUSGANGSSTROM IN A</b>  | 0-4200                   |
| <b>COMPATIBLE WITH MESHLE</b>                                    | No                       |