

PRODUCT NO. 5226

DOTLUX Mounting frame for ceiling mounting 620x620x70mm LED backlight panels



to the product page

- Installation frame for 620 mm LED panels in concrete ceilings, wooden ceilings and drywall ceilings
- Installation opening: 620 x 620 x 70mm
- The smooth surface ensures glare-free, homogeneous and shadow-free light distribution
- Compatible with Skylight motif panels

PRODUCT GROUP	EC000414_Leuchteneinbaugehäuse		
PREDECESSOR ARTICLE	2039-1	INSTALLATION OPENING WIDTH IN MM	624
		INSTALLATION OPENING LENGHT IN MM	624
WEIGHT IN KG	0.8	INPUT VOLTAGE SPAN	-
		WARRANTY IN YEARS	5
		SIMILAR TO RAL-COLOUR	9003
Dimensions		INPUT VOLTAGE RANGE LUMINAIRE	-
		APPLICATION	For in-situ concrete
length: 625mm		SUITABLE FOR HIGH VOLTAGE LUMINAIRES	Yes
width: 625mm		SUITABLE FOR LAMP POWER IN W	-
height: 70mm		SUITABLE FOR LED LUMINAIRES	Yes
		SUITABLE FOR LOW VOLTAGE LUMINAIRES	Yes
		WITH SPACE FOR GEAR	Yes
		MATERIAL	Aluminium
		BEG FUNDING	Only relevant in Germany
		ELDAS-NR.	941919349
		DIAMETER IN MM	0
		ABMESSUNGEN BREITE MM	625
		ABMESSUNGEN HÖHE MM	70
		INSTALLATION HEIGHT/DEPTH IN MM	70