

PRODUCT NO. 5068-M

LED power supply QUICK-FIXadapt CC 12-44W 300-1050mA dimmable DALI-2



to the product page

- The power supply unit is dimmable via DALI-2
- With constant current technology (CC), it is suitable for luminaires with constant current
- The connected constant current luminaires can be dimmed between 1%-100
- The output current is adjustable:
300/350/400/450/500/550/600/650/700/750/800/850/900/950/1000/1050mA
- The power supply unit is set to 500mA as standard
- Incl. magnets for mounting in conventional ceiling and wall luminaires
- Suitable for use in emergency lighting systems

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 4938

WEIGHT IN KG 0.16
POWER CONSUMPTION IN WATTS 12-44

Dimensions

length: 100mm
width: 43mm
height: 45mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	176 - 240 AC/DC
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	80
PROTECTION CLASS	II
OVERVOLTAGE PROTECTION	2000 V
OUTPUT VOLTAGE	6-52
WARRANTY IN YEARS	2
DIMMING WITHOUT DIMMER	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	Yes
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No

DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR DC-VOLTAGE (PRIMARY SIDE)	No
SUITABLE FOR CONSTANT CURRENT	Yes
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	only relevant in Germany
ELDAS-NR.	941006249
DIAMETER IN MM	0
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-50
ABMESSUNGEN BREITE MM	43
ABMESSUNGEN HÖHE MM	45
Ausgangsstrom in A	
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	60
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	60