

PRODUCT NO. 5270

DOTLUX LED amplifier top-hat rail max. 480W for multi-channel LED strips 4 channels 4x 5A (12-24V)



to the product page

- AMPpro amplifier for multicolored LED strips
- Flexible input voltage 12-24 V DIN rail mounting
- Integrated protection circuit (overload, overheating, short circuit)
- Suitable for single-color, dual-color, RGB or RGBW constant voltage LED strips or modules

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -

WEIGHT IN KG 0.119

POWER CONSUMPTION IN WATTS 480

PROTECTION CLASS (IP) IP20

INRUSH CURRENT IN A 0

TC TEMPERATURE IN °C 85

SUITED FOR EMERGENCY LIGHTING No

OUTPUT VOLTAGE 12 - 24 DC

WARRANTY IN YEARS 5

DIMMING WITHOUT DIMMER No

DIMMING 0-10 V Yes

DIMMING 1-10 V No

DIMMING DALI No

DIMMING DMX No

DIMMING DSI No

DIMMING POTENTIOMETER (INTEGRATED) No

DIMMING LINESWITCH No

DIMMING MANUFACTURER'S PROPRIETARY SYSTEM No

DIMMING MAINS VOLTAGE MODULATION No

DIMMING PHASE CUT-OFF No

DIMMING PROGRAMMABLE No

DIMMING RF No

DIMMING SINE WAVE REDUCTION No

DIMMING TOUCH AND DIM No

Dimensions

height: 65mm

length: 115mm

width: 48mm

DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
MODEL	-
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR CONSTANT CURRENT	Yes
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	941934399 - LC3
DIAMETER IN MM	0
ABMESSUNGEN BREITE MM	48
ABMESSUNGEN HÖHE MM	65
Ausgangsstrom in A	