

PRODUCT NO. 5271-4

DOTLUX LED amplifier max. 720W for multicolored LED strips 4 channels 4x5 A (12-36V)



to the product page



- AMPpro amplifier for multicolored LED strips
- Flexible input voltage 12-36 V with screw connection
- Integrated protection circuit (overload, overheating, short circuit)
- Suitable for single-color, dual-color, RGB or RGBW constant voltage LED strips or modules

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 3948-3/3948-4

WEIGHT IN KG 0.123
POWER CONSUMPTION IN WATTS max.720

Dimensions

width: 45mm
height: 27mm
length: 175mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 AC
POWER FACTOR	0,98
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	85
SUITED FOR EMERGENCY LIGHTING	No
OUTPUT VOLTAGE	12 - 36 DC
INPUT VOLTAGE SPAN	230
WARRANTY IN YEARS	3
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	230
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No

DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
MODEL	-
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR CONSTANT CURRENT	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	941934429
Dimension Length in mm	
DIAMETER IN MM	0
ABMESSUNGEN BREITE MM	45
ABMESSUNGEN HÖHE MM	27
Ausgangsstrom in A	