

PRODUCT NO. 5274

**DOTLUX DMX receiver/dimmer with integrated stand-alone function 4 channels 12-24V DC 4x5A
DIN rail**



to the product page

- Digital numerical display, DMX start address setting via buttons.
- Flexible input voltage 12-24V with screw connection
- RDM function can realize communication between DMX master and decoder.
- DMX preset for 1/2 or 4 color stripes
- More suitable for video recording due to adjustable PWM frequency 2000/500Hz
- More attractive dimming effects thanks to adjustable dimming curve (logarithmic or linear)
- Stand-alone mode for RGB/RGBW and 4-channel dimmer. Built-in programs instead of the DMX signal
- Suitable for single-color, dual-color, RGB or RGBW constant voltage LED strips or modules
- Integrated protection circuit (overload, overheating, short circuit)

PRODUCT GROUP	EC002924_Steuergerät für Leuchten	PROTECTION CLASS (IP)	IP20
SUCCESSION ARTICLE	-	OUTPUT VOLTAGE	12 - 24 DC
WEIGHT IN KG	0.12	WARRANTY IN YEARS	3
		CONTROL METHOD	DMX
		SUITABLE FOR MOUNTING	No
		COMPATIBLE WITH CASAMBI	No
		COMPATIBLE WITH APPLE HOMEKIT	Yes
Dimensions		COMPATIBLE WITH GOOGLE ASSISTANT	No
length: 115mm		COMPATIBLE WITH AMAZON ALEXA	No
width: 48mm		BEG FUNDING	Only relevant in Germany
height: 67mm		ELDAS-NR.	941934439
		Dimension Length in mm	
		DIAMETER IN MM	0
		ABMESSUNGEN BREITE MM	48
		ABMESSUNGEN HÖHE MM	67