

PRODUCT NO. 5280

DOTLUX LED radio receiver/dimmer for monochrome LED strips Fusion technology 1x15 A 12-48V DC



to the product page



- LED radio receiver/dimmer for monochrome LED strips
- Optimum compatibility for video recordings, as flicker-free dimming 0-100% with adjustable PWM frequency (250/500/2000/8000Hz)
- Logarithmic or linear dimming curve can be preset on the receiver
- One Fusion controller accepts up to 10 remote controls simultaneously
- Additional, wired push button control input
- Overheat/overload/short-circuit protection, automatic recovery
- The wireless DOTLUX Fusion technology is almost infinitely scalable and enables safe operation thanks to the MESH protocol
- All Fusion devices are compatible with each other and allow full flexibility for your project

PRODUCT GROUP	EC002924_Steuergerät für Leuchten	PROTECTION CLASS (IP)	IP20
SUCCESSION ARTICLE	-	INPUT VOLTAGE SPAN	12-48 DC
PREDECESSOR ARTICLE	3953	WARRANTY IN YEARS	3
WEIGHT IN KG	0.1	CONTROL METHOD	other
Dimensions		SUITABLE FOR MOUNTING	No
height: 27mm		INPUT VOLTAGE RANGE LUMINAIRE	12-48 DC
length: 175mm		COMPATIBLE WITH CASAMBI	No
width: 45mm		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	Yes
		COMPATIBLE WITH AMAZON ALEXA	No
		SUITABLE FOR DOTLUX FUSION	Yes
		BEG FUNDING	Only relevant in Germany
		ELDAS-NR.	941934489
		Dimension Length in mm	
		DIAMETER IN MM	0
		ABMESSUNGEN BREITE MM	45
		ABMESSUNGEN HÖHE MM	27