

PRODUCT NO. 5296-098060

DOTLUX LED wall light BRICK 10W COLORselect black



to the product page

- Particularly soft lighting effect thanks to internal reflector creates a great atmosphere
- Robust, splash-proof housing made of aluminum and real glass offers the best protection for outdoor use with IP65
- Phase-cut dimmable and therefore also suitable for indoor use as a modern wall light
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal
- EasyBase platform enables quick and easy installation
- Vertical mounting also possible
- Housing color similar to RAL 9005

PRODUCT GROUP EC002892_Decken-/Wandleuchte

WEIGHT IN KG 0.83
NET LUMINOUS FLUX IN LUMENS 750
LUMEN PER WATT 75
POWER CONSUMPTION IN WATTS 10

Dimensions

width: 100mm
height: 60mm
length: 200mm

BEAM ANGLE 60x115x40
PROTECTION CLASS (IP) IP65
LIGHT COLOR white
INPUT VOLTAGE 186 - 240 AC/DC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 3000/3500/4000
COLOR-RENDERING-INDEX CRI > 82
POWER FACTOR 0,9
INRUSH CURRENT IN A 0
LUMEN PER WATT 75
PROTECTION CLASS I
VOLTAGE TYPE AC/DC
HOUSING COLOUR black
SUITED FOR EMERGENCY LIGHTING No
SWITCH CYCLES > 100.000
INSTALLATION OPENING LENGHT IN MM 0
INPUT VOLTAGE SPAN 240
WARRANTY IN YEARS 3
L80/B10 25000
RATED CURRENT 0.14
SIMILAR TO RAL-COLOUR 9005
SUITABLE FOR SURFACE MOUNTING Yes
SUITABLE FOR MOUNTING No
INPUT VOLTAGE RANGE LUMINAIRE 240

ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	25000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	50000
WITH ILLUMINANT	No
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
MATERIAL COVER	Glass matt/satinized
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	Yes
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	Yes
DIMMING PHASE CUT-OFF	Yes
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	Yes
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	2
IMPACT STRENGTH	IK03
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	750 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Ending
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0

COLOUR OF LIGHT ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	10
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	50000
LIFETIME L90/B10 AT 25°C	13000
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	E
ELDAS-NR.	941200789
DIAMETER IN MM	0
MAX. SYSTEM POWER IN W	10
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	45
ABMESSUNGEN BREITE MM	100
ABMESSUNGEN HÖHE MM	60
INSTALLATION HEIGHT/DEPTH IN MM	0
NOMINAL VOLTAGE IN V	230
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	119
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	119
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
TYPE OF GRID	Matt
LIGHT OUTLET	Indirect
SURFACE PROTECTION HOUSING	Powder coating
LIGHT SHARING	Double asymmetric
LIGHT DISTRIBUTOR	Other
BEAM ANGLE	Open beam/diffuse
CONNECTION TYPE	Other