

PRODUCT NO. 5234-140240

**DOTLUX LED floor lamp ASSISTsensor 60W 8750lm 4000K silver 5500lm up / 3250lm down**



to the product page

- High system efficiency of 145lm/W enables energy-saving workplace illumination with only 60W consumption
- Touch DIM glass panel with button for switching between the 4 operating modes (motion detector and daylight sensor can be activated and deactivated)
- Glare-free, homogeneous and shadow-free light distribution / smooth top surface (uplight: 5500 lm / downlight: 3250 lm)
- UGR <19 (suitable for VDU workstations in accordance with EN 12464-1) thanks to special microprismatic cover for optimum glare control (direct component)
- Better contrast rendition with very good color rendering and constant color temperature (3-step MacAdam binning)
- Silver RAL9006 metal/aluminum housing with heavy U-shaped steel base
- 1.8 m connection cable with IEC plug
- Replaceable light unit
- Environmentally friendly delivery of the luminaire in a compact package (can be stored on Euro pallets)

**PRODUCT GROUP** EC000300\_Stehleuchte

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	75x110
<b>WEIGHT IN KG</b>	14.25	<b>LIGHT COLOR</b>	white
<b>LUMEN PER WATT</b>	145	<b>INPUT VOLTAGE</b>	220 - 240 AC
<b>NET LUMINOUS FLUX IN LUMENS</b>	8750	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>POWER CONSUMPTION IN WATTS</b>	60	<b>COLOR TEMPERATURE IN KELVIN</b>	4000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,95
		<b>INRUSH CURRENT IN A</b>	0
		<b>LUMEN PER WATT</b>	145
<b>Dimensions</b>		<b>PROTECTION CLASS</b>	I
<b>height:</b> 1968mm		<b>VOLTAGE TYPE</b>	AC/DC
<b>length:</b> 610mm		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
<b>width:</b> 288mm		<b>GLARE-FREE</b>	UGR < 19
		<b>SWITCH CYCLES</b>	> 100.000
		<b>WARRANTY IN YEARS</b>	3
		<b>L80/B10</b>	40000
		<b>SIMILAR TO RAL-COLOUR</b>	9006
		<b>DIMMING WITHOUT DIMMER</b>	No
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>LIFETIME L80/B10 AT 25°C</b>	40000
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	80000
		<b>WITH ILLUMINANT</b>	Yes

<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	Yes
<b>SUITABLE FOR NUMBER OF LIGHT SOURCES</b>	1
<b>MATERIAL COVER</b>	Plastic matt/satinized
<b>TYPE OF CONTROL GEAR</b>	LED operating device current-controlled
<b>WITH CONTROL GEAR</b>	Yes
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	Yes
<b>DIMMING LINESWITCH</b>	Yes
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	Yes
<b>DIMMING MAINS VOLTAGE MODULATION</b>	Yes
<b>DIMMING PHASE CUT-OFF</b>	Yes
<b>DIMMING PROGRAMMABLE</b>	Yes
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	Yes
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	No
<b>LIGHT DISTRIBUTOR</b>	Diffuser lens/optic/panel
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM3
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	Yes
<b>WITH LIGHT SENSOR</b>	Yes
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	Yes
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG0
<b>LUMINOUS FLUX ADJUSTABLE</b>	Positions
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>ELECTRICAL CONNECTION WITH CONNECTOR SYSTEM</b>	Yes
<b>LUMINAIRE HEADS FLEXIBLE</b>	No
<b>DIRECT-/INDIRECT PROPORTION SEPARATELY CONTROLLABLE</b>	No
<b>ADJUSTABLE</b>	Nein
<b>EXCHANGEABLE CONTROL GEAR</b>	Yes
<b>SUITABLE FOR LAMP POWER IN W</b>	60
<b>LAMP TYPE</b>	LED exchangeable
<b>WITH DIMMER</b>	Yes
<b>WITH PRESENCE INDICATOR</b>	Yes
<b>WITH REFLECTOR</b>	No
<b>WITH SWITCH</b>	Yes
<b>WITH SEPARATE READING LIGHT</b>	No
<b>MATERIAL</b>	Aluminium

<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	Yes
<b>LIFETIME L70/B50 AT 25°C</b>	80000
<b>LIFETIME L90/B10 AT 25°C</b>	20000
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE</b>	C
<b>ELDAS-NR.</b>	941010419
<b>DIAMETER IN MM</b>	0
<b>MAX. SYSTEM POWER IN W</b>	60
<b>ABMESSUNGEN BREITE MM</b>	288
<b>ABMESSUNGEN HÖHE MM</b>	1968
<b>NOMINAL VOLTAGE IN V</b>	36
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>LIGHT OUTLET</b>	Direct/indirect
<b>TYPE OF GRID</b>	None
<b>HOUSING COLOUR</b>	silver
<b>LAMP HOLDER</b>	Other