

PRODUCT NO. 3542-340240-KOPF-B-Ware

**DOTLUX LED-Stehleuchte STUDIObutler 80W 4000K RA>82 - Kopf B-Ware**



to the product page

N

<b>PRODUCT GROUP</b>	EC000300_Stehleuchte		
<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	120x120
<b>PREDECESSOR ARTICLE</b>	3542-240240-KOPF	<b>INPUT VOLTAGE</b>	176 - 240 AC/DC
<b>WEIGHT IN KG</b>	3.8	<b>SERVICE LIFE</b>	approx. 50.000h at 60°C
<b>NET LUMINOUS FLUX IN LUMENS</b>	8800	<b>COLOR TEMPERATURE IN KELVIN</b>	4000
<b>POWER CONSUMPTION IN WATTS</b>	80	<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,98
		<b>PROTECTION CLASS</b>	I
<b>Dimensions</b>		<b>VOLTAGE TYPE</b>	AC/DC
<b>width:</b> 312mm		<b>SUITED FOR EMERGENCY LIGHTING</b>	yes
<b>height:</b> 80mm		<b>SWITCH CYCLES</b>	> 100.000
<b>length:</b> 695mm		<b>INPUT VOLTAGE SPAN</b>	110-240 V AC / 176-276 V DC
		<b>WARRANTY IN YEARS</b>	0
		<b>L80/B10</b>	50000
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	110-240 V AC / 176-276 V DC
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>LIFETIME L80/B10 AT 25°C</b>	50000
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	60000
		<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	Yes
		<b>DIMMING 1-10 V</b>	Yes
		<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
		<b>LIFETIME L70/B50 AT 25°C</b>	60000
		<b>BEG FUNDING</b>	Only relevant in Germany

Dimension Length in mm	
<b>DIAMETER IN MM</b>	0
<b>MAX. SYSTEM POWER IN W</b>	80
<b>ABMESSUNGEN BREITE MM</b>	312
<b>ABMESSUNGEN HÖHE MM</b>	80
<b>HOUSING COLOUR</b>	silver