

PRODUCT NO. 5390-M

LED power supply CC for QUICK-FIXadapt max. 26W 450-600mA 30-42V dimmable 1-10V



to the product page

- The power supply unit is dimmable via 1-10V
- With constant current technology (CC), it is suitable for luminaires with constant current
- The connected constant current luminaires can be dimmed between 10%-100
- The output current is adjustable: 450/500/550/600mA
- Magnetic feet for attachment to QUICK-FIXadapt

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 5133-M

WEIGHT IN KG 0.14

Dimensions

width: 45mm

height: 41mm

length: 115mm

POWER FACTOR	0,96
INRUSH CURRENT IN A	0
OUTPUT VOLTAGE	30 - 42 DC
WARRANTY IN YEARS	3
DIMMING WITHOUT DIMMER	yes
DIMMING 0-10 V	No
DIMMING 1-10 V	Yes
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No

COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	only relevant in Germany
ELDAS-NR.	941010549
DIAMETER IN MM	0
ABMESSUNGEN BREITE MM	45
ABMESSUNGEN HÖHE MM	41
Ausgangsstrom in A	