

PRODUCT NO. 5398-25

DOTLUX LED glass tube NANOTUBE 58.8cm 9W 4000K frosted



to the product page

- Excellent durability thanks to UV-resistant, non-yellowing glass
- Glass cover enables better lighting effect
- Simple replacement of fluorescent tubes with starter
- Full, optimum light output immediately after switching on
- Can only be ordered in packaging units, not available individually
- Minimum purchase 25 pieces / purchase interval 25 pieces

ENERGY
DOTLUX
5398-25

Energy efficiency class: **C**

9 kWh/1000h

2019/2015

PRODUCT GROUP EC001959_LED-Lampe/Multi-LED

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 1615-140180

WEIGHT IN KG 0.208
NET LUMINOUS FLUX IN LUMENS 1440
LUMEN PER WATT 160
POWER CONSUMPTION IN WATTS 9

Dimensions

diameter: 28mm
width: 28mm
height: 28mm
length: 602mm

BEAM ANGLE 220
DIMMABLE No
PROTECTION CLASS (IP) IP20
INPUT VOLTAGE 220 - 240 AC
BASE G13
COLOR TEMPERATURE IN KELVIN 4000
COLOR-RENDERING-INDEX CRI > 82
CONSTRUCTION T8
POWER FACTOR 0,96
INRUSH CURRENT IN A 0
LUMEN PER WATT 160
HOUSING COLOUR white
WARRANTY IN YEARS 3
L80/B10 30000
RATED CURRENT 0.04
DIMMING WITHOUT DIMMER No
ASSORTMENT Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 C
LIFETIME L80/B10 AT 25°C 30000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C 60000
COLOUR CONSISTENCY (MCADAM ELLIPSE) SDCM6
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471 RGO

COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
LAMP SHAPE	Tube, single-ended
FILAMENT LAMP	No
LAMP DESIGNATION	T8
REMOTE OPERATION POSSIBLE WITH REMOTE CONTROL	No
LIFETIME L70/B50 AT 25°C	60000
LIFETIME L90/B10 AT 25°C	15000
PULSE DURATION IN µS	0
LIGHT COLOUR ACCORDING TO EN 12464-1	neutral white 3300 to 5300 K
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	keine Freigabe
DIAMETER IN MM	28
LUMINOUS FLUX IN LM	1440
ABMESSUNGEN BREITE MM	28
ABMESSUNGEN HöHE MM	28
NOMINAL VOLTAGE IN V	230
BEAM ANGLE_	220
TYPE OF GLASS/COVER COLOUR	Opal White