

PRODUCT NO. 2355-540120

DOTLUX LED moisture-proof luminaire MISTRAL IP66 1240mm max36W 4000K frosted



to the product page

- Faster installation thanks to innovative luminaire design. Combination of LED gear tray and cover.
- Individually replaceable branded components for the lowest maintenance costs
- UV-stable, shatterproof IK08/IP66 polycarbonate housing with frosted cover ensures shadow-free light distribution
- 5-pole through-wired with two internal luminaire connection terminals
- 2 full cable glands & blanking plugs
- Stainless steel fasteners with integrated anti-theft device
- Mounting accessories supplied (chain/ceiling/wall mounting) incl. rear panel punchings
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in locations with a fire hazard (DIN EN 60598-2-24, VDE 0711-2-24)
- This LED luminaire is suitable for use in food processing plants.
- This means it can also be used in areas that are certified in accordance with the International Featured Standard (IFS) or British Retail Consortium (BRC).
- Sustainable product design thanks to easily replaceable components

PRODUCT GROUP EC002892...Decken-/Wandleuchte

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 2355-1 2355-140180 2355-340180
2355-440120

WEIGHT IN KG 1.8
LUMEN PER WATT 138/137/136/134
POWER CONSUMPTION IN WATTS 21/26/31/36
NET LUMINOUS FLUX IN LUMENS 2900/3575/4225/4845

Dimensions

height: 80mm
length: 1240mm
width: 100mm

BEAM ANGLE 120
PROTECTION CLASS (IP) IP66
LIGHT COLOR white
INPUT VOLTAGE 186 - 240 AC/DC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 4000
COLOR-RENDERING-INDEX CRI > 82
POWER FACTOR 0,9
INRUSH CURRENT IN A 0
IK PROTECTION IK08
LUMEN PER WATT 138/137/136/134
PROTECTION CLASS I
HOUSING COLOUR gray
SWITCH CYCLES > 100.000
FOOD-READY Yes
WARRANTY IN YEARS 5
L80/B10 50000
SUITABLE FOR MOUNTING No
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 not required
LIFETIME L80/B10 AT 25°C 50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C 100000

SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
MATERIAL COVER	Plastic matt/satinized
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM2
IMPACT STRENGTH	IK08
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
CONNECTION TYPE	Cable
LUMINOUS FLUX ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED not exchangeable
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	C
ELDAS-NR.	941007929
Dimension Length in mm	
DIAMETER IN MM	0
MAX. SYSTEM POWER IN W	36
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-45
ABMESSUNGEN BREITE MM	100

ABMESSUNGEN HöHE MM	80
NOMINAL VOLTAGE IN V	230
TYPE OF WIRING	Suitable for through wiring
COLOUR OF LIGHT ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
BEAM ANGLE	Extreme wide beam >80°