

PRODUCT NO. 4176-130120

DOTLUX LED downlight UNISIZE 10W 3000K



to the product page

- Surface-mounted light for all installation openings from 55-135mm
- Easy installation thanks to an optimized, infinitely removable and adjustable mounting bracket with safety catch / mounting aid
- Removable spring clips enable direct screwing to walls and ceilings
- Extremely space-saving design thanks to integrated ballast
- Stable light output thanks to non-yellowing PMMA light guide
- 1 kV overvoltage protection
- Integrated aluminum cooling housing

PRODUCT GROUP	EC001744_Downlight/Strahler/Flutlicht		
SUCCESSION ARTICLE	-	BEAM ANGLE	120
PREDECESSOR ARTICLE	4176-030120	PROTECTION CLASS (IP)	IP20
		LIGHT COLOR	white
WEIGHT IN KG	0.3	INPUT VOLTAGE	200 - 240 AC
POWER CONSUMPTION IN WATTS	8,85	SERVICE LIFE	approx. 30.000 h at 25°C
LUMEN PER WATT	101	COLOR TEMPERATURE IN KELVIN	3000
NET LUMINOUS FLUX IN LUMENS	1010	COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,7
		INRUSH CURRENT IN A	0.24
		LUMEN PER WATT	101
Dimensions		PROTECTION CLASS	II
height: 20mm		VOLTAGE TYPE	AC
length: 165mm		HOUSING COLOUR	white
width: 165mm		SUITED FOR EMERGENCY LIGHTING	No
diameter: 165mm		SWITCH CYCLES	> 60.000
		INSTALLATION OPENING WIDTH IN MM	55
		INSTALLATION OPENING DIAMETER IN MM	55-135
		INSTALLATION OPENING LENGHT IN MM	55
		INPUT VOLTAGE SPAN	220-240
		WARRANTY IN YEARS	2
		L80/B10	30000
		RATED CURRENT	0.05
		SIMILAR TO RAL-COLOUR	9016
		SUITABLE FOR SURFACE MOUNTING	Yes

SUITABLE FOR MOUNTING	Yes
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	220-240
ASSORTMENT	Ecoline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	30000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	60000
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	without
TYPE OF CONTROL GEAR	LED operating device current- controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK05
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	No

CONNECTION TYPE	Other open cable ends
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	No
SUITABLE FOR LIGHT-TRACK MOUNTING	No
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	10
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	60000
LIFETIME L90/B10 AT 25°C	15000
PULSE DURATION IN µS	20
BEG FUNDING	Only relevant in Germany
LED OPERATING CURRENT IN MA	62
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	E
ELDAS-NR.	941402599
DIAMETER IN MM	165
MAX. SYSTEM POWER IN W	10
LUMINOUS FLUX IN LM	1010
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-40
ABMESSUNGEN BREITE MM	165
ABMESSUNGEN HÖHE MM	20
INSTALLATION HEIGHT/DEPTH IN MM	16,5
NOMINAL VOLTAGE IN V	230
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	90
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	230
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
LIGHT OUTLET	Direct/indirect
REFLECTOR	Matt
ADJUSTABILITY	Not adjustable
BEAM ANGLE	Extreme wide beam >80°
SURFACE PROTECTION	Untreated
MATERIAL COVER	Other