

PRODUCT NO. 5509-060360

DOTLUX LED rescue light EXITflip max.3W 6000K incl. 6 pictograms 8h operation, Li-ion battery with self-test



to the product page

- ONE FOR ALL One order number for all arrow directions
- Replaceable Li-Ion battery guarantees a lighting time of 8 hours
- Various switching programs selectable: continuous or standby mode
- Wall/ceiling mounting with infinitely variable folding pictogram
- With the matching track adapter 5519, the EXITflip can be mounted in all 3-phase tracks
- Power consumption in standby mode less than 0.5 watts
- Power consumption in charging mode less than 3 watts
- Automatic self-test function with integrated operating status indicator LED
- Includes 6 standard pictograms arrow (left, right, up, down)

PRODUCT GROUP	EC001957_Sicherheitsleuchte		
SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.8	INPUT VOLTAGE	220 - 240 AC
POWER CONSUMPTION IN WATTS	3	SERVICE LIFE	approx. 25.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	18	RANGE OF SENSOR	30
LUMEN PER WATT	6	COLOR TEMPERATURE IN KELVIN	6000
		POWER FACTOR	0,3
		IK PROTECTION	IK10
		LUMEN PER WATT	6
Dimensions		PROTECTION CLASS	II
width: 43mm		VOLTAGE TYPE	AC
height: 230mm		HOUSING COLOUR	white
length: 328mm		PICTOGRAM INCLUDED	Yes
		WARRANTY IN YEARS	5
		L80/B10	25000
		RATED CURRENT	0.02
		SELF-TEST	Automatic self-test
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	25000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	50000
		WITH ILLUMINANT	Yes

TYPE OF CONTROL GEAR	LED operating device voltage-controlled
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
DEGREE OF PROTECTION (NEMA)	2
IMPACT STRENGTH	IK10
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
CONSTANT LIGHT OUTPUT (CLO)	Yes
CONNECTION TYPE	Unassembled connection cable
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED not exchangeable
WITH REMOTE CONTROL	No
LIFETIME L70/B50 AT 25°C	50000
LIFETIME L90/B10 AT 25°C	13000
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	G
ELDAS-NR.	941007679
DIAMETER IN MM	0
MAX. SYSTEM POWER IN W	3
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	0-45
ABMESSUNGEN BREITE MM	43
ABMESSUNGEN HÖHE MM	230
NOMINAL VOLTAGE IN V	230
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	335
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	335
TYPE OF WIRING	Suitable for through wiring
MATERIAL COVER	Other