

PRODUCT NO. 4965-030120-B-Ware

DOTLUX LED solar wall light FLASHwall with sensor 3.5W 3000K B-Goods



to the product page

- Solar lithium-ion battery light with motion sensor (2 selectable operating modes)
- Reliable and fast battery charging thanks to large SOLAR panel, also suitable for indirect light incidence
- Particularly insect-friendly lighting thanks to warm white LEDs and motion sensor
- High-quality, splash-proof aluminum housing with weather-resistant powder coating
- Large, homogeneously designed light surface enables glare-free light distribution
- Easy alignment of the light thanks to adjustable stainless steel mounting bracket
- Includes rechargeable battery (replaceable) and mounting accessories
- Motion sensor operating modes:
 - A) 15% permanent light intensity after sunset, 100% light intensity when moving (duration 15 seconds)
 - B) 0% light intensity after sunset, 100% light intensity on movement (duration 15 seconds)

PRODUCT GROUP EC002892_Decken-/Wandleuchte

WEIGHT IN KG 1.8
POWER CONSUMPTION IN WATTS 3,5
NET LUMINOUS FLUX IN LUMENS 250

Dimensions

length: 160mm
width: 180mm
height: 255mm

BEAM ANGLE 120
PROTECTION CLASS (IP) IP54
SERVICE LIFE approx. 30.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 3000
COLOR-RENDERING-INDEX CRI > 82
MOTION SENSOR Infrared, 6-10m, 120°
INRUSH CURRENT IN A 0
BATTERY RUNTIME 3h at 100% / 20h at 15%
PROTECTION CLASS III
HOUSING COLOUR gray
WARRANTY IN YEARS 0
CAPACITY OF BATTERY IN MAH 1500
ASSORTMENT Proline
IMPACT STRENGTH IK06
EXCHANGEABLE CONTROL GEAR No
LAMP TYPE LED not exchangeable
PULSE DURATION IN µS 0
DIAMETER IN MM 0
ABMESSUNGEN BREITE MM 180
ABMESSUNGEN HÖHE MM 255