

## **PRODUCT NO. 5449-030115**

## DOTLUX LED floodlight HLFsport 1800W 3000K dimmable 115\*35° beam angle

















to the product page

The compact high-performance floodlight HLFsport is ideal for sports fields and soccer pitches,

- Optimized, asymmetric light control enables glare-free game operation and insect protection ULR<0 with reduced number of floodlights at the same time
- Protection of neighbors from stray light due to special lens geometry
- Corrosion-resistant, powder-coated cast aluminum housing with pressure compensation and high IP/IK protection (IP66/IK08)
- Dali dimmable and therefore compatible with our radio receiver Art. 5007-1 ideal for retrofitting existing installations
- 7 years DOTLUX warranty with an above average lifetime: L80>90.000h
- Very high operational safety with integrated overvoltage protection 20kV
- This luminaire is flicker-free and therefore also suitable for high-definition (HD) television recordings
- Sustainable product design due to easily replaceable components
- Other light colors can be ordered from 1pc onwards
- $\bullet\,$  The floodlight can also be dimmed via DMX. But must be specified when ordering.

| SUCCESSION ARTICLE          | -      | PROTECTION CLASS (IP)  | IP66                          |
|-----------------------------|--------|--|-------------------------------|
|                             |        | LIGHT COLOR  | white                         |
| WEIGHT IN KG                | 36     | INPUT VOLTAGE  | 200 - 420V AC                 |
| LUMEN PER WATT              | 150    | SERVICE LIFE   | approx. ca. 90.000 h at 25° C |
| POWER CONSUMPTION IN WATTS  | 1800   | COLOR TEMPERATURE IN KELVIN  | 3000                          |
| NET LUMINOUS FLUX IN LUMENS | 271545 | COLOR-RENDERING-INDEX  | CRI > 70                      |
|                             |        | POWER FACTOR   | 0,95                          |
|                             |        | LUMEN PER WATT   | 150                           |
|                             |        | PROTECTION CLASS   | 1                             |
| Dimensions                  |        | HOUSING COLOUR   | black                         |
|                             |        | SWITCH CYCLES  | >180,000                      |
| height: 1054mm              |        | OVERVOLTAGE PROTECTION   | 20000                         |
| length: 756mm               |        | INPUT VOLTAGE SPAN   | 200-420V AC                   |
| width: 607mm                |        | WARRANTY IN YEARS  | 7                             |
|                             |        | INPUT VOLTAGE RANGE LUMINAIRE                                      | 200-420V AC                   |
|                             |        | ASSORTMENT   | Proline                       |
|                             |        | ENERGY EFFICIENCY CLASS<br>ACCORDING TO EU REGULATION<br>2019/2015 | not required                  |
|                             |        | ETIM GRUPPEN-ID  | EC001744                      |
|                             |        | MATERIAL COVER   | Glass transparent             |
|                             |        | DIMMING DALI   | Yes                           |
|                             |        | NO DIM FUNCTION  | No                            |

**ELLIPSE**)

**COLOUR CONSISTENCY (MCADAM** 

SDCM6



COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL No

POSSIBLE BEG FUNDING

only relevant in Germany

ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE

COLOUR OF LIGHT ADJUSTABLE

No