

PRODUCT NO. 4865-130036

**DOTLUX LED floodlight LENSplus 100W 3000K 30\*60° beam angle**



to the product page

- Large variety of different beam angles enables optimum illumination for every situation
- Reliable operation thanks to highly efficient Lumileds® LEDs with 3-step MacAdam binning
- Solid, waterproof, ADC12 die-cast aluminum housing with pressure equalization valve (IP 66/IK08) and high-quality powder coating from Akzo Nobel
- ESG glass "ULTRA CLEAR" highly transparent glass for excellent light color and improved light output
- Durable industrial power supply units with 10kV overvoltage protection
- Curved mounting bracket enables easy installation without having to dismantle the bracket (freely rotatable 320°)
- Easy installation thanks to cable connector
- Replaceable components therefore repairable
- Sustainable product design thanks to easily replaceable components

<b>PRODUCT GROUP</b>	EC001744_Downlight/Strahler/Flutlicht		
<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	30x60
<b>PREDECESSOR ARTICLE</b>	4865-030036	<b>PROTECTION CLASS (IP)</b>	IP66
		<b>LIGHT COLOR</b>	white
<b>WEIGHT IN KG</b>	3.27	<b>INPUT VOLTAGE</b>	176 - 240 AC/DC
<b>LUMEN PER WATT</b>	126	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>POWER CONSUMPTION IN WATTS</b>	100	<b>COLOR TEMPERATURE IN KELVIN</b>	3000
<b>NET LUMINOUS FLUX IN LUMENS</b>	12630	<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,98
		<b>LUMEN PER WATT</b>	126
<b>Dimensions</b>		<b>PROTECTION CLASS</b>	I
<b>width:</b> 295mm		<b>VOLTAGE TYPE</b>	AC/DC
<b>height:</b> 71mm		<b>HOUSING COLOUR</b>	black
<b>length:</b> 370mm		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
		<b>SWITCH CYCLES</b>	> 100.000
		<b>OVERVOLTAGE PROTECTION</b>	up to 10000 V
		<b>WARRANTY IN YEARS</b>	7
		<b>L80/B10</b>	50000
		<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
		<b>SUITABLE FOR MOUNTING</b>	No
		<b>DIMMING WITHOUT DIMMER</b>	No
		<b>ENABLED LICENSED PRODUCT</b>	Yes
		<b>ASSORTMENT</b>	Highline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>LIFETIME L80/B10 AT 25°C</b>	50000

<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	100000
<b>WITH ILLUMINANT</b>	Yes
<b>SUITABLE FOR WALL MOUNTING</b>	Yes
<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
<b>SUITABLE FOR CEILING MOUNTING</b>	Yes
<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
<b>LAMP HOLDER</b>	-
<b>MATERIAL COVER</b>	Glass transparent
<b>TYPE OF CONTROL GEAR</b>	LED operating device current-controlled
<b>WITH CONTROL GEAR</b>	Yes
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	No
<b>LIGHT DISTRIBUTOR</b>	Focal lens
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>IMPACT STRENGTH</b>	IK08
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>TYPE OF WIRING</b>	Ending
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>SUITABLE FOR LOW VOLTAGE CABLE SYSTEM</b>	No
<b>SUITABLE FOR CLAMP-MOUNTING</b>	Yes
<b>SUITABLE FOR LIGHT-TRACK MOUNTING</b>	No
<b>SUITABLE FOR PEDESTAL/FLOOR MOUNTING</b>	Yes
<b>SUITABLE FOR TRAVERSE MOUNTING</b>	Yes
<b>EXCHANGEABLE CONTROL GEAR</b>	Yes
<b>LAMP TYPE</b>	LED exchangeable

<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>SURFACE BRUSHED</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE</b>	D
<b>ELDAS-NR.</b>	941502909
<b>MAX. SYSTEM POWER IN W</b>	100
<b>LUMINOUS FLUX IN LM</b>	12630
<b>ABMESSUNGEN BREITE MM</b>	295
<b>ABMESSUNGEN HÖHE MM</b>	71
<b>NOMINAL VOLTAGE IN V</b>	230
<b>MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16</b>	6
<b>MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16</b>	8
<b>LIGHT SHARING</b>	Asymmetric
<b>LIGHT OUTLET</b>	Direct
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>ADJUSTABILITY</b>	Swivelling
<b>SURFACE PROTECTION</b>	Powder coating
<b>BEAM ANGLE</b>	Wide beam 41-80°
<b>CONNECTION TYPE</b>	Other