

PRODUCT NO. 5795-099090

DOTLUX LED surface-mounted light PANELbig-ugr 295x1195mm 34W COLORselect with 4-pin plug for HCL incl. power supply unit



to the product page

- High-quality, powder-coated and visually appealing metal housing without visible screws
- Extremely simple installation with specially developed base plate with pre-mounted power supply unit
- Tool-free SLIDE-IN locking mechanism with spring steel clip
- Floating mounting (10mm) possible with supplied spacers
- Quick-connect terminal with through-wiring option
- Durable construction thanks to non-yellowing PMMA light guide technology ensures color-stable light output
- One article number - three light colors adjustable via COLORselect
- Suitable for HCL (HCL power supply unit and control unit required)
- Suitable for wall and ceiling mounting
- To be able to use COLORselect with the optional, dimmable power supply units, except for CASAMBI-HCL (4941-XXX), article 4860-SCHALTER is required
- The mounted spacer enables floating installation, which is particularly advantageous for uneven ceilings (e.g. old buildings)

PRODUCT GROUP EC002892_Decken-/Wandleuchte

SUCCESSION ARTICLE 5795-199090

WEIGHT IN KG 4.36

POWER CONSUMPTION IN WATTS 34

NET LUMINOUS FLUX IN LUMENS 4100/4300/4200

LUMEN PER WATT 120/126/124

BEAM ANGLE 90

PROTECTION CLASS (IP) IP40

LIGHT COLOR white

INPUT VOLTAGE 186 - 240 AC/DC

SERVICE LIFE approx. 50.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 3000/4000/5700

COLOR-RENDERING-INDEX CRI > 82

POWER FACTOR 0,96

LUMEN PER WATT 120/126/124

PROTECTION CLASS I

VOLTAGE TYPE AC

HOUSING COLOUR white

SUITED FOR EMERGENCY LIGHTING No

FOOD-READY Yes

INSTALLATION OPENING WIDTH IN MM 0

WARRANTY IN YEARS 5

L80/B10 50000

RATED CURRENT 1.05

SUITABLE FOR SURFACE MOUNTING Yes

SUITABLE FOR MOUNTING No

HCL-READY yes

Dimensions

length: 1195mm

width: 295mm

height: 43mm

ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	other Without
MATERIAL COVER	Plastic, structured
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	Yes
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM3
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK04
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING WITH MOVEMENT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
CONNECTION TYPE	Push-in clamp

PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0
COLOUR OF LIGHT ADJUSTABLE	Positions
LUMINOUS FLUX ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	34
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	D
ELDAS-NR.	941100079
DIAMETER IN MM	0
MAX. SYSTEM POWER IN W	34
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-40
ABMESSUNGEN BREITE MM	295
ABMESSUNGEN HÖHE MM	43
NOMINAL VOLTAGE IN V	230
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	23
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	38
LIGHT OUTLET	Direct
TYPE OF WIRING	Suitable for through wiring
BEAM ANGLE ADJUSTABLE	No
TYPE OF GRID	Matt
LIGHT SHARING	Symmetric
SURFACE PROTECTION HOUSING	Powder coating
LIGHT DISTRIBUTOR	None
BEAM ANGLE	Extreme wide beam >80°