

PRODUCT NO. 5893-099105

**DOTLUX Surface-mounted LED light SOFTEDGE 23W/29W/35W/40W COLORselect POWERselect IP44 1200mm**



to the product page

- Professional wall and ceiling light with large illuminated surface creates a uniform and ceiling-brightening light distribution
- Color-stable and glare-free thanks to prismatic, non-yellowing PMMA diffuser (IK07)
- One luminaire for all performance requirements: POWERSELECT in 4 levels (23W /29W /35W /40W)
- Simply set your favorite color yourself: DOTLUX COLORselect makes it easy to choose between different light colors (3000K/ 4000K/ 6000K)
- Tool-free quick-connect terminal (through-wirable with integrated strain relief)
- Flexible cable entry possible at the back and front
- Simple, flexible installation with 4 different mounting options
- Suitable for central battery

**PRODUCT GROUP** EC002892\_Decken-/Wandleuchte

**SUCCESSION ARTICLE** -

**WEIGHT IN KG** 2.3  
**POWER CONSUMPTION IN WATTS** 23 / 29 / 35 / 40  
**NET LUMINOUS FLUX IN LUMENS** 3220 - 5600  
**LUMEN PER WATT** 140

**BEAM ANGLE** 105  
**PROTECTION CLASS (IP)** IP44  
**LIGHT COLOR** white  
**INPUT VOLTAGE** 186 - 240 AC/DC  
**SERVICE LIFE** approx. 100,000 h at 25°C  
**COLOR TEMPERATURE IN KELVIN** 3000/4000/6000  
**COLOR-RENDERING-INDEX** CRI > 82  
**POWER FACTOR** 0,9  
**INRUSH CURRENT IN A** 0  
**LUMEN PER WATT** 140  
**PROTECTION CLASS** I  
**VOLTAGE TYPE** AC  
**HOUSING COLOUR** white  
**SUITED FOR EMERGENCY LIGHTING** yes  
**GLARE-FREE** UGR < 22  
**SWITCH CYCLES** > 200.000  
**INPUT VOLTAGE SPAN** 180-264  
**WARRANTY IN YEARS** 5  
**L80/B10** 100000  
**RATED CURRENT** 0.11  
**SUITABLE FOR SURFACE MOUNTING** Yes  
**SUITABLE FOR MOUNTING** No

**Dimensions**

**length:** 1195mm  
**width:** 150mm  
**height:** 52mm

<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	180-264
<b>ASSORTMENT</b>	Proline
<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
<b>LIFETIME L80/B10 AT 25°C</b>	100000
<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	200000
<b>WITH ILLUMINANT</b>	Yes
<b>SUITABLE FOR WALL MOUNTING</b>	Yes
<b>SUITABLE FOR SUSPENDED MOUNTING</b>	Yes
<b>SUITABLE FOR CEILING MOUNTING</b>	Yes
<b>SUITABLE FOR LIGHT LINE CONFIGURATION</b>	Yes
<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
<b>SUITABLE FOR NUMBER OF LIGHT SOURCES</b>	1
<b>LAMP HOLDER</b>	other Without
<b>MATERIAL COVER</b>	Plastic matt/satinized
<b>TYPE OF CONTROL GEAR</b>	LED operating device current-controlled
<b>WITH CONTROL GEAR</b>	Yes
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM4
<b>DEGREE OF PROTECTION (NEMA)</b>	2
<b>IMPACT STRENGTH</b>	IK07
<b>LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24</b>	Yes
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
<b>WITH MOVEMENT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>WITH AIR SLOTS</b>	No
<b>FILAMENT TEST ACCORDING TO IEC 60695-2-11</b>	650 °C - 30 s
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	No

<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG0
<b>COLOUR OF LIGHT ADJUSTABLE</b>	Positions
<b>LUMINOUS FLUX ADJUSTABLE</b>	Positions
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	No
<b>SUITABLE FOR LAMP POWER IN W</b>	23 / 29 / 35 / 40
<b>LAMP TYPE</b>	LED not exchangeable
<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	200000
<b>LIFETIME L90/B10 AT 25°C</b>	50000
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE</b>	C
<b>ELDAS-NR.</b>	941100129
<b>DIAMETER IN MM</b>	0
<b>MAX. SYSTEM POWER IN W</b>	40
<b>RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C</b>	-20-40
<b>ABMESSUNGEN BREITE MM</b>	150
<b>ABMESSUNGEN HÖHE MM</b>	52
<b>NOMINAL VOLTAGE IN V</b>	230
<b>MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16</b>	56
<b>MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16</b>	60
<b>LIGHT OUTLET</b>	Direct
<b>TYPE OF WIRING</b>	Suitable for through wiring
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>SURFACE PROTECTION HOUSING</b>	Powder coating
<b>TYPE OF GRID</b>	None
<b>LIGHT DISTRIBUTOR</b>	None
<b>BEAM ANGLE</b>	Extreme wide beam >80°
<b>CONNECTION TYPE</b>	Other