

PRODUCT NO. 6074

LED power supply CC for QUICK-FIXdc 2-50W 100-1050mA 20-54V DALI dimmable NFC linear adjustable current 350mA-1050mA via dip switch



to the product page

- DALI-2 certified LED driver, 1-100 % dimming range
- SELV output protection for safety and flexibility in luminaires
- Amplitude dimming for the highest quality of light output, in accordance with the IEEE 1789 recommendation
- NFC technology for wireless programming
- Suitable for use in emergency lighting applications
- Ideal solution for Class I and Class II
- Settings selectable via dip switch: 350/400/500/600/700/800/900/1050mA

PRODUCT GROUP	EC002710_LED-Betriebsgerät		
SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.24	INPUT VOLTAGE	176 - 240 AC/DC
POWER CONSUMPTION IN WATTS	6-50	POWER FACTOR	0,98
		INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	85
		PROTECTION CLASS	II
Dimensions		OVERVOLTAGE PROTECTION	1000 V
length: 360mm		OUTPUT VOLTAGE	20 - 54 DC
width: 30mm		INPUT VOLTAGE SPAN	198-264
height: 21mm		WARRANTY IN YEARS	5
		INPUT VOLTAGE RANGE LUMINAIRE	198-264
		DIMMING DALI	Yes
		DIMMING WITH PUSH-BUTTON	Yes
		NO DIM FUNCTION	No
		COMPATIBLE WITH CASAMBI	No
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No
		PULSE DURATION IN µS	0
		BEG FUNDING	only relevant in Germany
		ELDAS-NR.	941007739
		DIAMETER IN MM	0
		ABMESSUNGEN BREITE MM	30

ABMESSUNGEN HöHE MM	21
Ausgangsstrom in A	
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	36
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	60