

PRODUCT NO. 5124-1

CASAMBI Gateway for up to 2 networks



to the product page

- Hardware gateway for convenient operation of up to 2 Casambi networks
- Programming of the gateway and sites functionality in the Casambi app
- Remote access via Ethernet or WIFI
- The gateway can be used for remote diagnostics, network monitoring or remote control
- Range max. 30m in free field
- HDMI cable and power supply included in the scope of delivery
- USB mouse for easy commissioning
- External LTE antenna

PRODUCT GROUP	EC001099_Bussystem-Systemschnittstelle/Medien-Gateway	PROTECTION CLASS (IP)	IP20
SUCCESSION ARTICLE	-	INPUT VOLTAGE	220 - 240 AC
PREDECESSOR ARTICLE	ohne 5.Ghz	VOLTAGE TYPE	AC
WEIGHT IN KG	0.52	INPUT VOLTAGE SPAN	100-240
		WARRANTY IN YEARS	1
		INPUT VOLTAGE RANGE LUMINAIRE	100-240
Dimensions		MODEL	Multiple interfaces
length: 108mm		BUS SYSTEM RADIO BUS	No
width: 104mm		BUS SYSTEM KNX	No
height: 28mm		BUS SYSTEM KNX-RF (FUNK)	No
		BUS SYSTEM LON	No
		BUS SYSTEM POWERNET	No
		BEG FUNDING	Only relevant in Germany
		ELDAS-NR.	526000000
		DIAMETER IN MM	0
		ABMESSUNGEN BREITE MM	104
		ABMESSUNGEN HöHE MM	28
		MOUNTING METHOD	Other