

PRODUCT NO. 2822-940120-B-Ware

DOTLUX LED moisture-proof luminaire MISTRALsensor IP66 1540mm 38W Powerselect 4000K frosted with radar sensor



to the product page

- Faster installation due to new luminaire design. Combination of LED gear tray and cover.
- Individually replaceable brand-name components for lowest maintenance costs.
- UV-stable, shatterproof IK08/IP66 polycarbonate housing with frosted cover ensures shadow-free light distribution
- 5-pole through-wired with two internal luminaire terminals
- 2 full cable glands & blanking plugs
- Rustproof stainless steel catches with integrated anti-theft device
- Mounting accessories included (chain/ceiling/wall mounting) incl. rear panel punchings
- POWERselect: Dimmable in 10 steps of approx. 2.5 watts each (18-42 watts via dip switch in the luminaire) additionally via remote control 50-100%.
- The 5139 remote control is needed to set the sensor. Any number of luminaires can be set with one remote control. From a mounting height of 4m we recommend the long range remote control 5452.
- Three different functions of the high-frequency sensor are possible:
 1. on/off function via sensor then 0% light intensity
 2. on/off function via sensor with adjustable afterglow duration/brightness
 3. ON function via sensor followed by permanent basic brightness (10% / 30% brightness)
- In addition, the following values can be set in steps:
 - range (25/50/100% up to 7m)
 - Daylight sensor (5 / 15 / 50Lux / deactivated)
 - Light duration (5s / 1min / 5min / 10min)
 - Afterglow duration (0s / 1min / 30min / permanent)
 - Afterglow brightness (10% / 30%)
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in fire hazard areas (DIN EN 60598-2-24, VDE 0711-2-24) This LED luminaire is suitable for use in food processing plants.
- It can therefore also be used in areas certified according to the International Featured Standard (IFS) or British Retail Consortium (BRC).
- Sustainable, repairable product design

PRODUCT GROUP EC002892_Decken-/Wandleuchte

PREDECESSOR ARTICLE 2822-840120

WEIGHT IN KG 2.4

POWER CONSUMPTION IN WATTS 39

NET LUMINOUS FLUX IN LUMENS 5390

LUMEN PER WATT 138

BEAM ANGLE 120

PROTECTION CLASS (IP) IP66

INPUT VOLTAGE 176 - 240 AC/DC

SERVICE LIFE approx. 50.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 4000

COLOR-RENDERING-INDEX CRI > 82

MOTION SENSOR Radar, corridor-plus-function

POWER FACTOR 0,97

INRUSH CURRENT IN A 0

LUMEN PER WATT 138

Dimensions

length: 1540mm
width: 100mm
height: 80mm

PROTECTION CLASS	I
HOUSING COLOUR	gray
SUITED FOR EMERGENCY LIGHTING	yes
SWITCH CYCLES	> 100.000
FOOD-READY	Yes
WARRANTY IN YEARS	0
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK08
SUITABLE FOR EMERGENCY LIGHTING	Yes
EXCHANGEABLE CONTROL GEAR	Yes
LAMP TYPE	LED exchangeable
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
DIAMETER IN MM	0
ABMESSUNGEN BREITE MM	100
ABMESSUNGEN HöHE MM	80