


PRODUCT NO. 6298-057038

DOTLUX LED recessed light SUNLIGHT 620x310mm 47W 5700K



to the product page

- Simulates natural sunlight thanks to asymmetrical light distribution
- Most natural color rendering CRI > 92 for demanding users
- High-quality, powder-coated and visually appealing metal housing
- Glare-free working thanks to UGR<19 (suitable for VDU workstations)
- Durable construction thanks to non-yellowing PMMA lenses ensures color-stable light output
- Suitable for ceiling mounting
- Mounting on grid & drywall ceiling possible
- 25cm installation depth required
- The luminaire is supplied with a power supply unit and mounting clips

PRODUCT GROUP EC002892_Decken-/Wandleuchte

SUCCESSION ARTICLE -

WEIGHT IN KG 3.5
POWER CONSUMPTION IN WATTS 47
NET LUMINOUS FLUX IN LUMENS 2500
LUMEN PER WATT 43

Dimensions

width: 310mm
height: 192mm
length: 620mm

BEAM ANGLE 38
PROTECTION CLASS (IP) IP20
LIGHT COLOR white
INPUT VOLTAGE 220 - 240 AC
COLOR TEMPERATURE IN KELVIN 5700
COLOR-RENDERING-INDEX CRI > 90
POWER FACTOR 0,9
LUMEN PER WATT 43
PROTECTION CLASS II
VOLTAGE TYPE AC
HOUSING COLOUR white
SUITED FOR EMERGENCY LIGHTING No
GLARE-FREE UGR < 19
SWITCH CYCLES > 160.000
INSTALLATION OPENING WIDTH IN MM 290
INSTALLATION OPENING LENGHT IN MM 600
INPUT VOLTAGE SPAN 220-240
WARRANTY IN YEARS 5
L80/B10 50000
RATED CURRENT 0.25
SUITABLE FOR SURFACE MOUNTING Yes
SUITABLE FOR MOUNTING Yes
ENABLED LICENSED PRODUCT Yes
INPUT VOLTAGE RANGE LUMINAIRE 220-240

ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	Yes
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
LAMP HOLDER	-
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	Yes
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Focal lens
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK02
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	No
CONNECTION TYPE	Push-in clamp
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0

OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	47
LAMP TYPE	LED not exchangeable
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	G
ELDAS-NR.	941007399
MAX. SYSTEM POWER IN W	47
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	40
ABMESSUNGEN BREITE MM	310
ABMESSUNGEN HÖHE MM	192
INSTALLATION HEIGHT/DEPTH IN MM	190
NOMINAL VOLTAGE IN V	230
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	22
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	37
LIGHT SHARING	Asymmetric
LIGHT OUTLET	Direct
TYPE OF WIRING	Suitable for through wiring
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
TYPE OF GRID	White
SURFACE PROTECTION HOUSING	Powder coating
BEAM ANGLE	Medium beam 21-40°
MATERIAL COVER	Other