


PRODUCT NO. 3845-050036-B-Ware

DOTLUX LED-Tracklight SLIMtrack 20-28W 5000K TRUE COLOR black



to the product page

- Vibrant and high-contrast colors thanks to DOTLUX "TRUE COLOR" technology - always true colors
- Compatible with EUTRAC and almost all other 3-phase tracks
- Uniform light colors through 3-step MacAdam color sorting
- "Stay-cool" LED chip technology enables a modern, slim housing design with constant light Output
- One item - 4 power levels adjustable (20W / 24W / 26W / 28W factory preset)
- High quality aluminum housing with powder coating (RAL9005)
- Tool-less exchangeable high-performance reflectors with bayonet lock
- Branded ballast from OSRAM
- Sustainable, repairable product design

PRODUCT GROUP	EC001744_Downlight/Strahler/Flutlicht		
SUCCESSION ARTICLE	-	BEAM ANGLE	36
WEIGHT IN KG	1.2	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	max. 28	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	max. 2670	INPUT VOLTAGE	220 - 240 AC
LUMEN PER WATT	95	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	5000
		COLOR-RENDERING-INDEX	CRI > 95 TRUECOLOR
		POWER FACTOR	0,9
Dimensions		INRUSH CURRENT IN A	0
length: 312mm		IK PROTECTION	IK06
width: 85mm		LUMEN PER WATT	95
height: 85mm		PROTECTION CLASS	II
diameter: 85mm		VOLTAGE TYPE	AC
		HOUSING COLOUR	black
		GLARE-FREE	UGR < 19
		INSTALLATION OPENING WIDTH IN MM	85
		INSTALLATION OPENING DIAMETER IN MM	78
		INSTALLATION OPENING LENGHT IN MM	135
		INPUT VOLTAGE SPAN	220-240
		WARRANTY IN YEARS	0
		RATED CURRENT	0.16
		SIMILAR TO RAL-COLOUR	9005
		SUITABLE FOR SURFACE MOUNTING	No
		SUITABLE FOR MOUNTING	No

DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	220-240
ASSORTMENT	Highline
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	50000
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	-
MATERIAL COVER	Plastic matt/satinized
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Reflector
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK06
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No

IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	No
SUITABLE FOR LIGHT-TRACK MOUNTING	Yes
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	-
LAMP TYPE	LED exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	50000
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
LED OPERATING CURRENT IN MA	160
ROTATABLE / SWIVELLING	355° / 85°
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	E
Dimension Length in mm	
DIAMETER IN MM	85
MAX. SYSTEM POWER IN W	28
LUMINOUS FLUX IN LM	2670
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-65
ABMESSUNGEN BREITE MM	85
ABMESSUNGEN HÖHE MM	85
INSTALLATION HEIGHT/DEPTH IN MM	135
NOMINAL VOLTAGE IN V	230
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	44
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	66
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
ADJUSTABILITY	Rotating and swivelling
SURFACE PROTECTION	Powder coating
BEAM ANGLE	Medium beam 21-40°
REFLECTOR	Other
TYPE OF CONTROL GEAR	Not required
CONNECTION TYPE	Solder