

PRODUCT NO. 6355-12

LED power supply unit CV 12V/DC 20W 0-1.67A SELV IP20



to the product page

- Super-flat LED power supply unit
- Flicker-free design
- Output is SELV-compliant and protected against short circuit, overload and overheating.

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 4249-12

WEIGHT IN KG 0.07
POWER CONSUMPTION IN WATTS 20

Dimensions

length: 121mm
width: 45mm
height: 16mm

| | |
|--|--------------|
| PROTECTION CLASS (IP) | IP20 |
| INPUT VOLTAGE | 220 - 240 AC |
| POWER FACTOR | 0,85 |
| INRUSH CURRENT IN A | 30 |
| TC TEMPERATURE IN °C | 85 |
| PROTECTION CLASS | II |
| OUTPUT VOLTAGE | 12 DC |
| INPUT VOLTAGE SPAN | 198-264 |
| WARRANTY IN YEARS | 3 |
| DIMMING WITHOUT DIMMER | No |
| INPUT VOLTAGE RANGE LUMINAIRE | 198-264 |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | No |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |

| | |
|--|--------------------------|
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| NO DIM FUNCTION | Yes |
| CONSTANT LIGHT OUTPUT (CLO) | No |
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| MODEL | Static |
| SUITABLE FOR CONSTANT VOLTAGE | Yes |
| SUITABLE FOR OUTDOOR USE | No |
| SUITABLE FOR CONSTANT CURRENT | No |
| HOUSING | Plastic housing |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| PULSE DURATION IN μS | 50 |
| BEG FUNDING | Only relevant in Germany |
| ELDAS-NR. | 919990059 |
| DIAMETER IN MM | 0 |
| ABMESSUNGEN BREITE MM | 45 |
| ABMESSUNGEN HÖHE MM | 16 |
| Ausgangsstrom in A | |
| MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16 | 56 |
| MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16 | 95 |