

PRODUCT NO. 5917-030120-B-Ware

DOTLUX Wall light MORPHO 6W 3000K black B-Goods



to the product page

- Modern, decorative wall light with direct and indirect lighting
- Unique design with great decorative effect
- Robust, splash-proof aluminum housing offers the best protection for outdoor use with IP65 certification
- Excellent heat management thanks to the aluminum housing ensures a long service life

PRODUCT GROUP	EC002892_Decken-/Wandleuchte		
SUCCESSION ARTICLE	-	BEAM ANGLE	120
WEIGHT IN KG	0.69	PROTECTION CLASS (IP)	IP65
POWER CONSUMPTION IN WATTS	6	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	322	INPUT VOLTAGE	220 - 240 AC
LUMEN PER WATT	53	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 80
Dimensions		POWER FACTOR	0,85
length: 200mm		INRUSH CURRENT IN A	0
width: 100mm		IK PROTECTION	IK05
height: 80mm		LUMEN PER WATT	53
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	black
		WARRANTY IN YEARS	0
		L80/B10	55000
		SIMILAR TO RAL-COLOUR	9005
		LIFETIME L80/B10 AT 25°C	55000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	82500
		SUITABLE FOR WALL MOUNTING	Yes
		SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
		MATERIAL COVER	Plastic, transparent
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No

DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK05
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	750 °C - 30 s
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	82500
LIFETIME L90/B10 AT 25°C	27500
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
Dimension Length in mm	
DIAMETER IN MM	0
ABMESSUNGEN BREITE MM	100
ABMESSUNGEN HÖHE MM	80
COLOUR OF LIGHT ADJUSTABLE	No
BEAM ANGLE	Extreme wide beam >80°