

PRODUCT NO. 6557-040080

**DOTLUX CONNECT upright accessories via jack 12W 4000K**



to the product page

- Simply plug in an additional upright via a jack plug to create atmospheric backlighting.
- Reduces the glare of the LED luminaire and lowers the UGR value to below 19, ideal for a workplace environment.
- Sleek and timeless appearance matches various interior styles.
- The luminaires can be installed with virtually no gap between them to create a continuous, uninterrupted line of light.

<b>PRODUCT GROUP</b>	EC000109_Lichtleiste		
<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	120
<b>WEIGHT IN KG</b>	0.43	<b>PROTECTION CLASS (IP)</b>	IP20
<b>NET LUMINOUS FLUX IN LUMENS</b>	1440	<b>LIGHT COLOR</b>	white
<b>POWER CONSUMPTION IN WATTS</b>	12	<b>INPUT VOLTAGE</b>	220 - 240 AC
<b>LUMEN PER WATT</b>	120	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	4000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>IK PROTECTION</b>	IK06
		<b>LUMEN PER WATT</b>	120
<b>Dimensions</b>		<b>PROTECTION CLASS</b>	I
<b>length:</b> 1122mm		<b>VOLTAGE TYPE</b>	AC
<b>width:</b> 54mm		<b>HOUSING COLOUR</b>	black
<b>height:</b> 11mm		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
		<b>INPUT VOLTAGE SPAN</b>	220-240
		<b>WARRANTY IN YEARS</b>	5
		<b>L80/B10</b>	50000
		<b>RATED CURRENT</b>	0.4
		<b>SIMILAR TO RAL-COLOUR</b>	9005
		<b>ENABLED LICENSED PRODUCT</b>	Yes
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	220-240
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>LIFETIME L80/B10 AT 25°C</b>	50000
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	100000

<b>WITH ILLUMINANT</b>	Yes
<b>LAMP HOLDER</b>	-
<b>TYPE OF CONTROL GEAR</b>	LED operating device current-controlled
<b>WITH CONTROL GEAR</b>	No
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>LIGHT DISTRIBUTOR</b>	Reflector
<b>DEGREE OF PROTECTION (NEMA)</b>	1
<b>IMPACT STRENGTH</b>	IK06
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	No
<b>TYPE OF WIRING</b>	Ending
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	No
<b>SUITABLE FOR LAMP POWER IN W</b>	12
<b>LAMP TYPE</b>	LED not exchangeable
<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE</b>	A
<b>ELDAS-NR.</b>	941600969
Dimension Length in mm	
<b>MAX. SYSTEM POWER IN W</b>	12
<b>ABMESSUNGEN BREITE MM</b>	54
<b>ABMESSUNGEN HÖHE MM</b>	11
<b>NOMINAL VOLTAGE IN V</b>	36

<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>CONNECTION TYPE</b>	Other