


PRODUCT NO. 6584-040120-B-Ware

DOTLUX LED refurbishment light QUICK-FIXpico 1.5W 4000K B-Goods



to the product page

- 1.5W luminaire-in-luminaire system with 190lm in 3000K or 4000K
- Secure mounting via neodymium magnet, screw fixing possible
- Direct connection to 230 V AC or 176 - 276 V DC (suitable for central battery)
- With its compact dimensions of just 7.5 cm long and 2.5 cm wide, there is a suitable place for it anywhere
- Always with you: the perfect daily companion for a wide range of applications, e.g. adding emergency power functions to existing lights, orientation light, switch cabinet lighting or interior furniture lighting
- Use of several QUICK-FIXpico possible through parallel connection

Attention: B-goods, magnets can fall off under heavy use, screw connection still possible

PRODUCT GROUP	EC002892_Decken-/Wandleuchte		
WEIGHT IN KG	0.023	BEAM ANGLE	120
NET LUMINOUS FLUX IN LUMENS	190	PROTECTION CLASS (IP)	IP20
LUMEN PER WATT	125	LIGHT COLOR	white
POWER CONSUMPTION IN WATTS	1,5	INPUT VOLTAGE	176 - 276 AC/DC
		SERVICE LIFE	approx. 50.000 h at 25°C
		OUTPUT LUMEN DURING EMERGENCY	190
		COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 82
Dimensions		POWER FACTOR	0,5
width: 25mm		LUMEN PER WATT	125
height: 20mm		PROTECTION CLASS	II
length: 75mm		VOLTAGE TYPE	AC/DC
		HOUSING COLOUR	colourless
		SUITED FOR EMERGENCY LIGHTING	yes
		INSTALLATION OPENING WIDTH IN MM	0
		INPUT VOLTAGE SPAN	176-276
		WARRANTY IN YEARS	0
		L80/B10	50000
		RATED CURRENT	0
		SUITABLE FOR SURFACE MOUNTING	Yes
		SUITABLE FOR MOUNTING	No
		INPUT VOLTAGE RANGE LUMINAIRE	176-276
		POWER EMERGENCY OPERATION IN W	1,5

ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
MOUNTING LOCATION	Indoor
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	No
LAMP HOLDER	-
SURFACE PROTECTION HOUSING	-
MATERIAL COVER	Plastic matt/satinized
TYPE OF GRID	-
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM5
DEGREE OF PROTECTION (NEMA)	1
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	Yes
WITH AIR SLOTS	No
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Ending
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0
BEAM ANGLE ADJUSTABLE	-

OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	1.5
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
BEG FUNDING	only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	D
MAX. SYSTEM POWER IN W	1,5
ABMESSUNGEN BREITE MM	25
ABMESSUNGEN HÖHE MM	20
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	960
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	960
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
LIGHT SHARING	Symmetric
BEAM ANGLE	Extreme wide beam >80°