


PRODUCT NO. 5259-130360

DOTLUX LED bollard light WAY 100cm 7,5/15W 3000K



to the product page

- Freely selectable light emission surface thanks to interchangeable glass and cover plates
- Power-Select enables the system output to be set to 50% / 100%
- High-quality aluminum housing with powder coating in DB703
- Robust, splash-proof design for outdoor use with IP 54 protection
- Glare-free and homogeneous light distribution with high color rendering Ra>82
- EASYbase platform enables quick and easy installation
- For looping through with connection box (input and output each for 3 x 2.5 mm² cable)
- Incl. professional mounting base made of special aluminum alloy for better hold, approved for installation with earth contact

PRODUCT GROUP	EC000301_Wegeleuchte		
SUCCESSION ARTICLE	-	BEAM ANGLE	360
PREDECESSOR ARTICLE	5259-030360	PROTECTION CLASS (IP)	IP65
		LIGHT COLOR	white
WEIGHT IN KG	5.13	SERVICE LIFE	approx. 40.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	400/800	COLOR TEMPERATURE IN KELVIN	3000
POWER CONSUMPTION IN WATTS	7,5-15	COLOR-RENDERING-INDEX	CRI > 82
LUMEN PER WATT	53	IK PROTECTION	IK06
		LUMEN PER WATT	53
Dimensions		PROTECTION CLASS	I
length: 120mm		VOLTAGE TYPE	AC/DC
width: 120mm		HOUSING COLOUR	anthracite
height: 950mm		WARRANTY IN YEARS	5
		L80/B10	40000
		DIMMING WITHOUT DIMMER	No
		ENABLED LICENSED PRODUCT	Yes
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	40000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	80000
		WITH ILLUMINANT	Yes
		LAMP HOLDER	-
		MATERIAL COVER	Glass transparent

TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK06
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
CONSTANT LIGHT OUTPUT (CLO)	No
CONNECTION TYPE	other cables
BEAM ANGLE ADJUSTABLE	Positions
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	15
LAMP TYPE	LED exchangeable
LIFETIME L70/B50 AT 25°C	80000
LIFETIME L90/B10 AT 25°C	20000
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	G
ELDAS-NR.	941700899
DIMENSION LENGTH IN MM	120
MAX. SYSTEM POWER IN W	15
ABMESSUNGEN BREITE MM	120
ABMESSUNGEN HÖHE MM	950
NOMINAL VOLTAGE IN V	230
LIGHT OUTLET	Direct
TYPE OF WIRING	Suitable for through wiring
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
LIGHT SHARING	Symmetric/asymmetric
SURFACE PROTECTION	Powder coating
LIGHT DISTRIBUTOR	Other
BEAM ANGLE	Extreme wide beam >80°