

PRODUCT NO. 5402-B-Ware

DOTLUX LED glass tube NANOTUBE 150cm 24W 4000K frosted B-goods



to the product page



- Excellent durability thanks to UV-resistant, non-yellowing glass
- Glass cover enables better lighting effect
- Simple replacement of fluorescent tubes with starter
- Full, optimum light output immediately after switching on

PRODUCT GROUP EC001959_LED-Lampe/Multi-LED

PREDECESSOR ARTICLE 1937-340180 3201-1

WEIGHT IN KG 0
POWER CONSUMPTION IN WATTS 24
NET LUMINOUS FLUX IN LUMENS 3840
LUMEN PER WATT 160

Dimensions

BEAM ANGLE 220
DIMMABLE No
PROTECTION CLASS (IP) IP20
INPUT VOLTAGE 220 - 240 AC
BASE G13
COLOR TEMPERATURE IN KELVIN 4000
COLOR-RENDERING-INDEX CRI > 82
CONSTRUCTION T8
POWER FACTOR 0,98
INRUSH CURRENT IN A 0
LUMEN PER WATT 160
HOUSING COLOUR white
WARRANTY IN YEARS 0
L80/B10 30000
RATED CURRENT 0.11
DIMMING WITHOUT DIMMER No
LIFETIME L80/B10 AT 25°C 30000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C 60000
COLOUR CONSISTENCY (MCADAM ELLIPSE) SDCM2
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471 RG0
COMPATIBLE WITH APPLE HOMEKIT No
COMPATIBLE WITH GOOGLE ASSISTANT No

COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
LAMP SHAPE	Tube, single-ended
FILAMENT LAMP	No
LAMP DESIGNATION	T8
REMOTE OPERATION POSSIBLE	No
WITH REMOTE CONTROL	No
LIFETIME L70/B50 AT 25°C	60000
LIFETIME L90/B10 AT 25°C	15000
PULSE DURATION IN µS	0
LIGHT COLOUR ACCORDING TO EN 12464-1	neutral white 3300 to 5300 K
BEG FUNDING	Only relevant in Germany
LUMINOUS FLUX IN LM	3840
NOMINAL VOLTAGE IN V	230
BEAM ANGLE	220
TYPE OF GLASS/COVER	Opal
COLOUR	White