

PRODUCT NO. 4936-2

DOTLUX LED power supply QUICK-FIXadapt CC 300-1050mA max.42 W



to the product page

- Non-dimmable power supply unit for QUICK-FIXadapt
- incl. magnetic attachment
- Input voltage: 220-240 V AC
- Output voltage: 25 - 42 V DC
- The temperature range at which the power supply unit can be used is between -20°C and 40°C.
- The cable length of the power supply unit is 24cm.
- Adjustable to 300mA, 350mA, 400mA, 450mA, 500mA, 550mA, 600mA, 650mA, 700mA, 750mA, 800mA, 900mA, 950mA, 1000mA, 1050mA via dip switch
- The driver is preset to 700mA

PRODUCT GROUP EC002710_LED-Betriebsgerät

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 4936-1

WEIGHT IN KG 0.123
POWER CONSUMPTION IN WATTS 16-33

Dimensions

length: 97mm
width: 43mm
height: 36mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	186 - 240 AC/DC
POWER FACTOR	0,96
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	85
PROTECTION CLASS	II
SUITED FOR EMERGENCY LIGHTING	yes
OUTPUT VOLTAGE	25 - 42 DC
WARRANTY IN YEARS	5
DIMMING WITHOUT DIMMER	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No

DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
SUITABLE FOR OUTDOOR USE	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	only relevant in Germany
ELDAS-NR.	941009609
Dimension Length in mm	
DIAMETER IN MM	0
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-+50
ABMESSUNGEN BREITE MM	43
ABMESSUNGEN HÖHE MM	36
Ausgangsstrom in A	