

PRODUCT NO. 5234-140240-B-Ware

**DOTLUX LED floor lamp ASSISTsensor 60W 8750lm 4000K silver 5500lm up / 3250lm down B-goods**



to the product page

- High system efficiency of 145lm/W enables energy-saving workplace illumination with only 60W consumption
- Touch DIM glass panel with button for switching between the 4 operating modes (motion detector and daylight sensor can be activated and deactivated)
- Glare-free, homogeneous and shadow-free light distribution / smooth top surface (uplight: 5500 lm / downlight: 3250 lm)
- UGR <19 (suitable for VDU workstations in accordance with EN 12464-1) thanks to special microprismatic cover for optimum glare control (direct component)
- Better contrast rendition with very good color rendering and constant color temperature (3-step MacAdam binning)
- Silver RAL9006 metal/aluminum housing with heavy U-shaped steel base
- 1.8 m connection cable with IEC plug
- Replaceable light unit
- Environmentally friendly delivery of the luminaire in a compact package (can be stored on Euro pallets)

**PRODUCT GROUP** EC000300\_Stehleuchte

**WEIGHT IN KG** 14.25  
**POWER CONSUMPTION IN WATTS** 60  
**NET LUMINOUS FLUX IN LUMENS** 8750  
**LUMEN PER WATT** 145

**BEAM ANGLE** 75x110  
**LIGHT COLOR** white  
**INPUT VOLTAGE** 100 - 240 AC  
**SERVICE LIFE** approx. 50.000 h at 25°C  
**COLOR TEMPERATURE IN KELVIN** 4000  
**COLOR-RENDERING-INDEX** CRI > 82  
**POWER FACTOR** 0,95  
**INRUSH CURRENT IN A** 0  
**LUMEN PER WATT** 145  
**PROTECTION CLASS** I  
**VOLTAGE TYPE** AC/DC  
**GLARE-FREE** UGR < 19  
**SWITCH CYCLES** > 100.000  
**WARRANTY IN YEARS** 0  
**L80/B10** 40000  
**SIMILAR TO RAL-COLOUR** 9006  
**DIMMING WITHOUT DIMMER** No  
**ENABLED LICENSED PRODUCT** Yes  
**ASSORTMENT** Proline  
**LIFETIME L80/B10 AT 25°C** 40000  
**LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C** 80000  
**WITH ILLUMINANT** Yes

**Dimensions**

**length:** 610mm  
**width:** 288mm  
**height:** 1968mm

<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	Yes
<b>SUITABLE FOR NUMBER OF LIGHT SOURCES</b>	1
<b>MATERIAL COVER</b>	Plastic matt/satinized
<b>WITH CONTROL GEAR</b>	Yes
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	Yes
<b>DIMMING LINESWITCH</b>	Yes
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	Yes
<b>DIMMING MAINS VOLTAGE MODULATION</b>	Yes
<b>DIMMING PHASE CUT-OFF</b>	Yes
<b>DIMMING PROGRAMMABLE</b>	Yes
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	Yes
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	No
<b>LIGHT DISTRIBUTOR</b>	Diffuser lens/optic/panel
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM3
<b>WITH MOVEMENT SENSOR</b>	Yes
<b>WITH LIGHT SENSOR</b>	Yes
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	Yes
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG0
<b>LUMINOUS FLUX ADJUSTABLE</b>	Positions
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>ELECTRICAL CONNECTION WITH CONNECTOR SYSTEM</b>	Yes
<b>LUMINAIRE HEADS FLEXIBLE</b>	No
<b>DIRECT-/INDIRECT PROPORTION SEPARATELY CONTROLLABLE</b>	No
<b>ADJUSTABLE</b>	Nein
<b>EXCHANGEABLE CONTROL GEAR</b>	Yes
<b>SUITABLE FOR LAMP POWER IN W</b>	60
<b>LAMP TYPE</b>	LED exchangeable
<b>WITH DIMMER</b>	Yes
<b>WITH PRESENCE INDICATOR</b>	Yes
<b>WITH REFLECTOR</b>	No
<b>WITH SWITCH</b>	Yes
<b>WITH SEPARATE READING LIGHT</b>	No
<b>MATERIAL</b>	Aluminium
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	Yes
<b>LIFETIME L70/B50 AT 25°C</b>	80000

<b>LIFETIME L90/B10 AT 25°C</b>	20000
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>DIAMETER IN MM</b>	0
<b>MAX. SYSTEM POWER IN W</b>	70
<b>ABMESSUNGEN BREITE MM</b>	288
<b>ABMESSUNGEN HÖHE MM</b>	1968
<b>NOMINAL VOLTAGE IN V</b>	36
<b>TYPE OF CONTROL GEAR</b>	Electronic transformer
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>LIGHT OUTLET</b>	Direct/indirect
<b>TYPE OF GRID</b>	None
<b>HOUSING COLOUR</b>	silver
<b>LAMP HOLDER</b>	Other