

PRODUCT NO. 6895

DOTLUX LED luminaire housing SURFACE Ø380



to the product page

- Flat, modern design with sturdy PMMA plastic cover
- Tool-free replacement with the QUICK-FIX luminaire-in-luminaire system
- Pre-assembled 5-pole quick-connect terminal for through-wiring
- Flexible mounting thanks to central and lateral cable feed-through
- Universal perforation with longitudinal slots on the base plate
- Compatible with all our QUICK-FIX refurbishment luminaires up to a diameter of Ø300mm
- Sustainable product design thanks to easily replaceable components
- Light transmission of 75% thanks to opal cover for optimum efficiency

PRODUCT GROUP EC000414_Leuchteneinbaugeschäfte

WEIGHT IN KG 0.64

Dimensions

diameter: 380mm

width: 380mm

height: 95mm

length: 380mm

INSTALLATION OPENING WIDTH IN MM	0
INSTALLATION OPENING LENGTH IN MM	0
WARRANTY IN YEARS	3
ASSORTMENT	Proline
APPLICATION	For slab ceiling
SUITABLE FOR HIGH VOLTAGE LUMINAIRES	Yes
SUITABLE FOR LAMP POWER IN W	15
SUITABLE FOR LED LUMINAIRES	Yes
SUITABLE FOR LOW VOLTAGE LUMINAIRES	No
WITH SPACE FOR GEAR	Yes
MATERIAL	Aluminium
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	941999969
DIAMETER IN MM	380
ABMESSUNGEN BREITE MM	380
ABMESSUNGEN HÖHE MM	95
INSTALLATION HEIGHT/DEPTH IN MM	0