


PRODUCT NO. 3379-140170-B-Ware

DOTLUX LED refurbishment light QUICK-FIXplus 12W 4000K



to the product page

- Our QUICK-FIX LED luminaires enable quick and easy refurbishment of existing wall and ceiling luminaires thanks to our innovative luminaire-in-luminaire system
- Extra-high magnetic feet enable installation above the existing cabling
- Very high efficiency of up to 160lm/W thanks to low-current LEDs and therefore long service life
- Special lenses with 170° beam angle ensure absolutely shadow-free light distribution even in larger luminaire housings up to 900 mm in diameter
- Our QUICK-FIXplus luminaires comply with DIN EN60598-2-22:2014, a standard that confirms approval in the field of emergency lighting
- Tool-free replacement of the LED luminaire even by a non-specialist thanks to AC system plug

PRODUCT GROUP EC002892_Decken-/Wandleuchte

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE 3379-040170

WEIGHT IN KG 0.172
POWER CONSUMPTION IN WATTS 12
NET LUMINOUS FLUX IN LUMENS 1900
LUMEN PER WATT 158

Dimensions

length: 180mm
width: 180mm
height: 40mm
diameter: 180mm

BEAM ANGLE 170
PROTECTION CLASS (IP) IP20
LIGHT COLOR white
INPUT VOLTAGE 186 - 240 AC/DC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 4000
COLOR-RENDERING-INDEX CRI > 82
POWER FACTOR 0,9
IK PROTECTION IK05
LUMEN PER WATT 158
PROTECTION CLASS II
VOLTAGE TYPE AC/DC
HOUSING COLOUR white
SUITED FOR EMERGENCY LIGHTING yes
SWITCH CYCLES > 100.000
WARRANTY IN YEARS 0
L80/B10 50000
RATED CURRENT 0.06
SUITABLE FOR SURFACE MOUNTING Yes
SUITABLE FOR MOUNTING No
ENABLED LICENSED PRODUCT Yes
ASSORTMENT Proline
MOUNTING LOCATION Indoor
LIFETIME L80/B10 AT 25°C 50000

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
MATERIAL COVER	Plastic, transparent
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM5
IMPACT STRENGTH	IK05
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	Yes
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	without
CONSTANT LIGHT OUTPUT (CLO)	No
TYPE OF WIRING	Ending
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No

IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
BEG FUNDING	only relevant in Germany
Dimension Length in mm	
DIAMETER IN MM	180
MAX. SYSTEM POWER IN W	12
ABMESSUNGEN BREITE MM	180
ABMESSUNGEN HÖHE MM	40
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	35
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	58
SURFACE PROTECTION HOUSING	Untreated
TYPE OF CONTROL GEAR	Electronic transformer
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
TYPE OF GRID	None
BEAM ANGLE	Extreme wide beam >80°