


PRODUCT NO. 7121-030120

**DOTLUX LED mirror light SKYLAR 9.5W 3000K black**



to the product page

- 3000K warm white light for natural and pleasant mirror lighting
- Modern, slim housing for an elegant bathroom look
- Ideal for bathrooms, guest WCs or dressing rooms
- Uniform illumination of the mirror without glare
- Magnetically detachable LED module for quick and easy installation
- Twistlock fastener ensures theft-proof and stable installation
- Triac dimmable for individual brightness adjustment
- Sustainable product design thanks to easily replaceable components

PRODUCT GROUP EC002892\_Decken-/Wandleuchte

**WEIGHT IN KG** 0.745  
**POWER CONSUMPTION IN WATTS** 9,5  
**NET LUMINOUS FLUX IN LUMENS** 710  
**LUMEN PER WATT** 74

**Dimensions**

**length:** 900mm  
**width:** 181mm  
**height:** 67mm

**BEAM ANGLE** 120  
**PROTECTION CLASS (IP)** IP44  
**LIGHT COLOR** white  
**INPUT VOLTAGE** 186 - 240 AC/DC  
**SERVICE LIFE** approx. 50.000 h at 25°C  
**COLOR TEMPERATURE IN KELVIN** 3000  
**COLOR-RENDERING-INDEX** CRI > 92  
**POWER FACTOR** 0,95  
**INRUSH CURRENT IN A** 0  
**LUMEN PER WATT** 74  
**PROTECTION CLASS** II  
**VOLTAGE TYPE** AC/DC  
**HOUSING COLOUR** black  
**SUITED FOR EMERGENCY LIGHTING** No  
**GLARE-FREE** UGR < 25  
**SWITCH CYCLES** > 100.000  
**INSTALLATION OPENING WIDTH IN MM** 0  
**INSTALLATION OPENING LENGHT IN MM** 0  
**WARRANTY IN YEARS** 3  
**L80/B10** 50000  
**RATED CURRENT** 0.06  
**SUITABLE FOR SURFACE MOUNTING** Yes  
**SUITABLE FOR MOUNTING** No  
**ENABLED LICENSED PRODUCT** Yes

<b>ASSORTMENT</b>	Proline
<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
<b>LIFETIME L80/B10 AT 25°C</b>	50000
<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	100000
<b>WITH ILLUMINANT</b>	Yes
<b>SUITABLE FOR WALL MOUNTING</b>	Yes
<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
<b>SUITABLE FOR CEILING MOUNTING</b>	No
<b>SUITABLE FOR LIGHT LINE CONFIGURATION</b>	No
<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
<b>SUITABLE FOR NUMBER OF LIGHT SOURCES</b>	1
<b>LAMP HOLDER</b>	-
<b>MATERIAL COVER</b>	Plastic matt/satinized
<b>TYPE OF CONTROL GEAR</b>	LED operating device current-controlled
<b>WITH CONTROL GEAR</b>	Yes
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	Yes
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	No
<b>LIGHT DISTRIBUTOR</b>	Diffuser lens/optic/panel
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM3
<b>IMPACT STRENGTH</b>	IK07
<b>LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24</b>	Yes
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>WITH AIR SLOTS</b>	No
<b>FILAMENT TEST ACCORDING TO IEC 60695-2-11</b>	650 °C - 30 s
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	No

<b>TYPE OF WIRING</b>	Ending
<b>CONNECTION TYPE</b>	Push-in clamp
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	Yes
<b>SUITABLE FOR LAMP POWER IN W</b>	9,5
<b>LAMP TYPE</b>	LED not exchangeable
<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	Yes
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE</b>	F
<b>ELDAS-NR.</b>	941260289
<b>DIAMETER IN MM</b>	0
<b>MAX. SYSTEM POWER IN W</b>	9,5
<b>RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C</b>	-20-45
<b>ABMESSUNGEN BREITE MM</b>	181
<b>ABMESSUNGEN HÖHE MM</b>	67
<b>INSTALLATION HEIGHT/DEPTH IN MM</b>	0
<b>MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16</b>	80
<b>MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16</b>	160
<b>LIGHT OUTLET</b>	Direct
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>TYPE OF GRID</b>	Other
<b>SURFACE PROTECTION HOUSING</b>	Other
<b>BEAM ANGLE</b>	Extreme wide beam >80°
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	Other
<b>DEGREE OF PROTECTION (NEMA)</b>	Other