


PRODUCT NO. 7122-030120

DOTLUX LED mirror light SKYLAR 9.5W 3000K silver



to the product page

- 3000K warm white light for natural and pleasant mirror lighting
- Modern, slim housing for an elegant bathroom look
- Ideal for bathrooms, guest WCs or dressing rooms
- Uniform illumination of the mirror without glare
- Magnetically detachable LED module for quick and easy installation
- Twistlock fastener ensures theft-proof and stable installation
- Triac dimmable for individual brightness adjustment
- Sustainable product design thanks to easily replaceable components

PRODUCT GROUP EC002892_Decken-/Wandleuchte

WEIGHT IN KG 0.74
POWER CONSUMPTION IN WATTS 9,5
NET LUMINOUS FLUX IN LUMENS 850
LUMEN PER WATT 90

Dimensions

length: 900mm
width: 181mm
height: 67mm

BEAM ANGLE 120
PROTECTION CLASS (IP) IP44
LIGHT COLOR white
INPUT VOLTAGE 186 - 240 AC/DC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 3000
COLOR-RENDERING-INDEX CRI > 92
POWER FACTOR 0,95
INRUSH CURRENT IN A 0
LUMEN PER WATT 90
PROTECTION CLASS II
VOLTAGE TYPE AC/DC
SUITED FOR EMERGENCY LIGHTING No
GLARE-FREE UGR < 25
SWITCH CYCLES > 100.000
INSTALLATION OPENING WIDTH IN MM 0
INSTALLATION OPENING LENGHT IN MM 0
WARRANTY IN YEARS 3
L80/B10 50000
RATED CURRENT 0.06
SUITABLE FOR SURFACE MOUNTING Yes
SUITABLE FOR MOUNTING No
ENABLED LICENSED PRODUCT Yes
ASSORTMENT Proline

| | |
|--|---|
| ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| LIFETIME L80/B10 AT 25°C | 50000 |
| LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C | 100000 |
| WITH ILLUMINANT | Yes |
| SUITABLE FOR WALL MOUNTING | Yes |
| SUITABLE FOR SUSPENDED MOUNTING | No |
| SUITABLE FOR CEILING MOUNTING | No |
| SUITABLE FOR LIGHT LINE CONFIGURATION | No |
| SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1 | No |
| SUITABLE FOR NUMBER OF LIGHT SOURCES | 1 |
| LAMP HOLDER | - |
| MATERIAL COVER | Plastic matt/satinized |
| TYPE OF CONTROL GEAR | LED operating device current-controlled |
| WITH CONTROL GEAR | Yes |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | No |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | Yes |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| DIMMING DEPENDING ON CONTROL GEAR | No |
| NO DIM FUNCTION | No |
| LIGHT DISTRIBUTOR | Diffuser lens/optic/panel |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM3 |
| IMPACT STRENGTH | IK07 |
| LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24 | Yes |
| SUITABLE FOR EMERGENCY LIGHTING | No |
| WITH MOVEMENT SENSOR | No |
| WITH LIGHT SENSOR | No |
| COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE | No |
| WITH AIR SLOTS | No |
| FILAMENT TEST ACCORDING TO IEC 60695-2-11 | 650 °C - 30 s |
| CONSTANT LIGHT OUTPUT (CLO) | No |
| TYPE OF WIRING | Ending |

| | |
|---|--------------------------|
| CONNECTION TYPE | Push-in clamp |
| OPERATION BY BLUETOOTH | No |
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| IFTTT SUPPORT AVAILABLE | No |
| EXCHANGEABLE CONTROL GEAR | Yes |
| SUITABLE FOR LAMP POWER IN W | 9,5 |
| LAMP TYPE | LED not exchangeable |
| EMERGENCY POWER SUPPLY INTEGRATED | No |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | Yes |
| DIMMING GPRS | No |
| LIFETIME L70/B50 AT 25°C | 100000 |
| LIFETIME L90/B10 AT 25°C | 25000 |
| PULSE DURATION IN µS | 0 |
| BEG FUNDING | Only relevant in Germany |
| ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE | F |
| ELDAS-NR. | 941260279 |
| DIAMETER IN MM | 0 |
| MAX. SYSTEM POWER IN W | 9,5 |
| RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C | -20-45 |
| ABMESSUNGEN BREITE MM | 181 |
| ABMESSUNGEN HÖHE MM | 67 |
| INSTALLATION HEIGHT/DEPTH IN MM | 0 |
| MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16 | 80 |
| MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16 | 160 |
| LIGHT OUTLET | Direct |
| COLOUR OF LIGHT ADJUSTABLE | No |
| LUMINOUS FLUX ADJUSTABLE | No |
| BEAM ANGLE ADJUSTABLE | No |
| LIGHT SHARING | Symmetric |
| TYPE OF GRID | Other |
| HOUSING COLOUR | silver |
| SURFACE PROTECTION HOUSING | Other |
| BEAM ANGLE | Extreme wide beam >80° |
| PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471 | Other |
| DEGREE OF PROTECTION (NEMA) | Other |