

PRODUCT NO. 7251

DOTLUX LED power supply max. 40W 150-1050mA tunable white NFC



to the product page

- Wide operating range of 150-1050mA for flexible adaptation to different luminaires and power requirements
- Support for DALI-2, Push DIM and Push CCT
- The output current can be precisely set contactlessly via NFC using an app
- The driver is preset to 150mA at the factory
- DT8

PRODUCT GROUP EC002710_LED-Betriebsgerät

WEIGHT IN KG 0.237

Dimensions

length: 278mm

width: 30mm

height: 16mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	176 - 240 AC/DC
POWER FACTOR	0,9
TC TEMPERATURE IN °C	75
PROTECTION CLASS	I
SUITED FOR EMERGENCY LIGHTING	yes
OUTPUT VOLTAGE	15-54
INPUT VOLTAGE SPAN	176-278
WARRANTY IN YEARS	5
DIMMING WITHOUT DIMMER	yes
INPUT VOLTAGE RANGE LUMINAIRE	176-278
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	Yes
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	Yes
NO DIM FUNCTION	No
SUITABLE FOR EMERGENCY LIGHTING	Yes
CONSTANT LIGHT OUTPUT (CLO)	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
MODEL	Dynamic
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR DC-VOLTAGE (PRIMARY SIDE)	Yes
SUITABLE FOR CONSTANT CURRENT	Yes
HOUSING	Metal housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
BEG FUNDING	Only relevant in Germany
ELDAS-NR.	941979199
DIAMETER IN MM	0
RATED AMBIENT TEMPERATURE ACCORDING TO IEC62722-2-1 IN °C	-20-55
ABMESSUNGEN BREITE MM	30
ABMESSUNGEN HÖHE MM	16
AUSGANGSSTROM IN A	0,15-1,05
MAX. NUMBER OF LIGHTS PER MINIATURE CIRCUIT BREAKER B16	66
MAX. NUMBER OF LIGHTS PER CIRCUIT BREAKER C16	66
COMPATIBLE WITH MESHLE	No