

DOTLUX LED tube LUMENPLUS 60cm 11W 5500K clear glass rotatable end cap

Order number: 1617

- *TECHNICAL ADVANTAGES*
 - Internal aluminum heat sink enables optimized thermal management
 - Polycarbonate cover with UV-protective coating (non-yellowing)
 - Future-oriented due to individually replaceable power supply units
 - Individually adjustable light beam angle due to patented end cap
 - Fail-safe because each individual LED is controlled separately
 - Suitable for central battery
- *FURTHER ADVANTAGES OF THE LUMENPLUS TUBES*
 - 5 years Dotlux warranty on driver and LEDs
 - Very easy replacement of fluorescent tubes with starter
 - Immediately the full, optimal light output after switching on
 - LM80 certified LEDs
 - This tube is VDE certified

Power consumption in watts: 11; Net luminous flux in lumens: 1430; Lumen per watt: 130; Beam angle: 120°; protection class (IP): IP20; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 5500; Color-rendering-index: CRI > 83; Lumen per watt: 130; Housing colour: multicoloured; Suited for emergency lighting: yes; Switch cycles: > 100.000; Input voltage span: 220-240 V AC; Warranty in years: 5; Input voltage range luminaire: 220-240 V AC; Energy efficiency class according to EU regulation 2019/2015: D; ETIM Gruppen-ID: EC001959; Colour consistency (McAdam ellipse): SDCM6; Suitable for emergency lighting: Yes; Light colour according to EN 12464-1: daylight white >5300 K; BEG funding: Only relevant in Germany; Colour: White diameter: 26mm