

**DOTLUX LED module ADQplus 24V 24pcs/light curtain IP65 115W per light curtain 6000K**

Order number: 2844

- Simple and solder-free installation in seconds, only at the corners of the light curtain thanks to large-area prefabricated modules
- Uniform LED spacing ensures optimum illumination of the advertising space
- Yellowing-proof water protection ensures stable light output
- High color rendering index (Ra>80)
- Separable after each light strip

Power consumption in watts: 115; Net luminous flux in lumens: 11500; Lumen per watt: 100; Beam angle: 120°; protection class (IP): IP65; Temperature range: -40°C to +40°C; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 6000; Color-rendering-index: CRI > 80; Lumen per watt: 100; Voltage type: DC; Switch cycles: > 100.000; Input voltage span: 24 V DC; Warranty in years: 5; Input voltage range luminaire: 24 V DC; Energy efficiency class according to EU regulation 2019/2015: F; ETIM Gruppen-ID: EC000996; Colour consistency (McAdam ellipse): SDCM6; Connection type: Cable; Photobiological safety according to EN 62471: RG1; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Suitable for traffic lights: No; Suitable for constant voltage: No; Suitable for general lighting: Yes; Suitable for constant current: Yes; Suitable for rail traffic: No; Suitable for matrix information boards: No; Suitable for variable road signs: No; Light colour according to EN 12464-1: daylight white >5300 K; BEG funding: Only relevant in Germany; LED-Betriebsstrom in mA: 5625; Shape: Rectangular; Colour: White width: 1000mm